
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2. WITHDRAL AT 0



| Product designation | | | | Selector switch actuator key - 3 position |
|--------------------------|-----------------------|-----|--------|---|
| Product type designation | | | | LPFS35 |
| General characteristics | S | | | |
| Colour | | | | Black |
| Type of positions | | | | Selector switch |
| Material | | | | Aluminium and zinc alloy |
| IEC degree of protection | on | | | IP66, IP67 and IP69K |
| Mechanical features | | | | |
| Mechanical life | | | cycles | 1000000 |
| Fixing | | | | Without mounting adapter |
| Mounting adapter | | | | LPXAU120M |
| UL technical data | | | | |
| UL degree of protection | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +70 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +85 |

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

cULus

ETIM classification

1/2





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2. WITHDRAL AT 0

ETIM 8.0

EC002611 -Control switch