

LUMINAIRES - SPOTS ENCASTRÉS / DOWNLIGHTS

EN-PLH18

Product Description:

La gamme de downlights extra-plat Slim-Fit™ a été conçue pour offrir une uniformité et un rendement lumineux supérieurs en utilisant la dernière technologie d'éclairage latéral. Avec seulement 25 mm de

Product Image:



Product Specs:

Technology	LED	Input Voltage	220-240V AC
Lamp Base	Aucun	Positional Adjustment	Fixe
Number of LEDs	90	Luminaire Distribution	Accentuation
Lifetime L70 (hrs)	25.000	Input Frequency	50/60HZ
Dimmable	Non	IP Rating	IP44
IK Rating	IK07	Acoustic Rated	No
Operating Env. Temp. (Min) °C	-20°C	Operating Env. Temp. (Max) °C	40°C
Power Factor	0.9	Overall Diameter (mm)	225
Height (mm)	25	Recess Depth (mm)	50
Cutout Diameter (mm)	206		

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	CRI	Colour	Finish Colour
EN-PLH18/30	18	110	1520	85	80	3000	Blanc mat
EN-PLH18/40	18	110	1650	92	80	4000	Blanc mat
EN-PLH18DA/30	18	110	1520	85	80	3000	Blanc mat
EN-PLH18DA/40	18	110	1650	92	80	4000	Blanc mat
EN-PLH18V/30	18	110	1520	85	80	3000	Blanc mat
EN-PLH18V/40	18	110	1650	92	80	4000	Blanc mat

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 228 700