
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1



			Selector switch
Product designation			actuator key - 3
			position
Product type designation			LPFS33
General characteristics			
Colour			Black
Type of positions			Selector switch
			Aluminium and
			zinc alloy for the
Material			metal part,
			polyamide for
			plastic parts
IEC degree of protection			IP66, IP67 and
			IP69K
Mechanical features			
Mechanical life		cycles	1000000
Fixing			Without mounting
			adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4,
or degree of protection			4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85
Dimensions			

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1

cULus

ETIM classification

ETIM 8.0 EC002611 - Control switch