

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: LENS UGR<19  
Colour: WHITE  
Dimming: PUSH, DALI  
Emergency: WITH ACCESSORY  
L: 595mm  
A: 595mm  
H: 14 (35 con alim.)mm  
Warranty: 5 years  
Weight: 3.37kg

## Tech data

Luminaire input power: 24W  
Luminaire luminous flux: 2665lm  
Luminous flux in emergency: 30%  
IP: 40  
Insulation class: I  
Supply voltage: 600 mA ALIMENT.INCLUSO  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 20W  
Source luminous flux: 3262lm  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[View more product info](#)


# SCHOOL

104118.01

novalux


ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES




SCHOOL: KIT INST.PLAFONE 600X600

104108.01




SCHOOL: KIT MOLLE PER INCASSO

104107.99




SCHOOL: KIT SOSPENSIONE H1200

104110.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



THE PANEL 2: KIT INST.INC.RAS.CART.600

102028.99



SCHOOL: KIT ANTICADUTA L=3000

104119.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.