

Panduit Cable Ties - Nylon 612

Specifications

Mechanical and chemical attributes of black weather resistant nylon 612 cable ties shall provide resistance to UV rays and chemical attack when exposed to various concentrations of salts, hydrocarbons, chlorinated hydrocarbons bases and acid rain.



Technical information

Tensile @ yield @ 73° F (psi)	9,300 per ISO 527
Water absorption (24 Hours)	0.4% per ASTM D570
Weathering Life Expectancy (Years) / UV Resistance	20*
Max. continuous use temperature	194°F (90°C) per UL 746B
Min. installation temperature	-4 °F (-20 °C) or +32 °F (0 °C)
Halogen-Free	Yes
Heat Deflection Temperature @ 1.8 Mpa	122° (50°C) per ASTM D648 ISO 75 - 1/-2
Chemical resistance	High
Salts	High
Hydrocarbons (Gas, Oil, Lubricants)	Excellent
Chlorinated Hydrocarbons	High
Base	High
Acid Rain	High
Impact Resistance	Good

Key Features and Benefits

Nylon 612 material	Resist chemical attack when exposed to salts, hydrocarbons, chlorinated hydrocarbons, bases, and corrosive (zinc chloride, and diluted acids), and low temperature indoor or outdoor applications.
Black UV resistant properties	Allows ties to withstand exposure to sunlight; contributes to weathering life expectancy of 20 years*
One-piece design with locking wedge	Provides low thread force for easy and reliable installation; improves productivity and reduces operator fatigue
Curved, tapered tip	Threads easily into head; installs quickly for improved productivity

Applications

Nylon 612 offers 20 years of weathering life expectancy and resistance to zinc chlorides and dilute acids. Ideal for wire management on galvanized surfaces / frames. Nylon 612 cable ties are suitable for outdoor applications where temperatures range from -76°F (-60°C) up to 194°F (90°C)

*This is an estimated life expectancy and not a guarantee of life in an application.

Nylon 612 Cable Ties

Miniature Cross Section 20lbs (89N) Min. Loop Tensile

Black Weather Resistant	PLT1M-M6120
--------------------------------	-------------

Intermediate Cross Section 25lbs (111N) Min. Loop Tensile

Black Weather Resistant	PLT1.5I-M6120
--------------------------------	---------------

Standard Cross Section 50lbs (222N) Min. Loop Tensile

Black Weather Resistant	PLT2S-M6120
	PLT2.5S-M6120
	PLT3S-M6120
	PLT4S-M6120

Light-Heavy Cross Section 120lbs (534N) Min. Loop Tensile

Black Weather Resistant	PLT4H-TL6120
	PLT7LH-C6120
	PLT8LH-C6120

Recommended Installation Tools

Hand Tools: Tool controlled tension and cut-off	GTS-E, GTH-E, GS2B-E, GS4H-E, GS4EH-E
Hand Tools: Installer controlled tension and cut-off	STS2, STH2, ST3EH
Pneumatic Tools	PTS, PPTS, PTH

Panduit Cable Ties - Nylon 612

Ordering Information

Black Weather Resistant Part Number	Length In. (mm)	Width In. (mm)	Thickness In. (mm)	Max. Bundle Dia. In. (mm)	Min. Loop Tensile Strength Lbs. (N)	Recommended Installation Tool	Pkg. Qty.*	Bulk Ctn. Qty.
-------------------------------------	-----------------	----------------	--------------------	---------------------------	-------------------------------------	-------------------------------	------------	----------------

Miniature Cross Section

PLT1M-M6120	3.9	.098	0.043	0.87	20	GTS-E, GS2B-E, PTS, PPTS, STS2	1,000	50,000
PLT1M-C6120	(99)	(2.5)	(1.1)	(22)	(89)		100	1,000

Intermediate Cross Section

PLT1.5I-M6120	5.6	0.142	0.045	1.38	25	GTS-E, GS2B-E, PTS, PPTS, STS2	1,000	25,000
PLT1.5I-C6120	(142)	(3.6)	(1.1)	(35)	(111)		100	1,000

Standard Cross Section

PLT2S-M6120	7.4	0.19 (4.8)	0.047 (1.2)	1.88	50 (222)	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	1,000	10,000
PLT2S-C6120	(188)			(48)			100	1,000
PLT2.5S-M6120	9.8		2.5	1,000			10,000	
PLT2.5S-C6120	(249)		(64)	100			1,000	
PLT3S-M6120	11.5		3.0	1,000			10,000	
PLT3S-C6120	(292)		(76)	100			1,000	
PLT4S-M6120	14.5		4.0	1,000			5,000	
PLT4S-C6120	(368)		(102)	100			1,000	

Light-Heavy Cross Section

PLT4H-TL6120	14.5 (368)	0.3 (7.6)	0.075 (1.9)	4.0 (102)	120 (534)	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	250	1,000
PLT7LH-C6120	24.7 (627)			7.0 (178)			100	2,000
PLT8LH-C6120	27.6 (701)			8.0 (203)				

* Order number of pieces required, in multiples of Packages Quantity

Related Products



Part Number	Used with Nylon 612 Cable Ties	Description	Std. Pkg. Qty.
Tool Controlled Tension and Cut-Off Tools			
GTS-E, GS2B-E	Miniature, Intermediate, Standard	Tool controlled tension tool consistently provide flush tie cut-offs to speed installation	1
GS4H-E, GTH-E	Standard, Light-Heavy		
GS4EH-E	Light-Heavy		
Installer Controlled Tension and Cut-Off Tools			
STS2	Miniature, Intermediate, Standard	Installer controlled tension tools are economical and ideal for low volume applications	1
STH2	Standard, Light-Heavy		
ST3EH	Light-Heavy		
Pneumatic Tools			
PTS, PPTS	Miniature, Intermediate, Standard	Pneumatic, push button operation tools tension and cut-off excess tie in a fraction of a second	1
PTH	Standard, Light-Heavy		

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT®

©2022 Panduit Corp.
ALL RIGHTS RESERVED.
CTSPO6-SA-ENG
Printed in the U.S.A.
6/2022