



**INDUCTIVE PROXIMITY SENSORS** 



## IQE17-07NNSKW2S | IQE

INDUCTIVE PROXIMITY SENSORS





#### Detailed technical data

#### Features

Housing	Rectangular housing
Housing	Rectangular housing
Dimensions (W x H x D)	17 mm x 17 mm x 29.5 mm
Sensing range S <sub>n</sub>	7 mm
Safe sensing range S <sub>a</sub>	5.67 mm
Installation type	Non-flush
Switching frequency	1,000 Hz
Connection type	Cable, 3-wire, 2 m
Switching output	NPN
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP67 <sup>1)</sup>

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	≤ 2 V
Time delay before availability	≤ 100 ms
Hysteresis	5 % 15 %
Reproducibility	< 3 %
Temperature drift (of S <sub>r</sub> )	± 10 %
EMC	According to EN 60947-5-2
Continuous current l <sub>a</sub>	≤ 200 mA
No load current	10 mA
Cable material	PVC
Short-circuit protection	1
Short-circuit protection Reverse polarity protection	J J

# IQE17-07NNSKW2S | IQE INDUCTIVE PROXIMITY SENSORS

Ambient operating temperature	-25 °C +75 °C
Housing material	Plastic
Tightening torque, max.	0.9 Nm
UL File No.	E348498

#### Safety-related parameters

MTTF <sub>D</sub>	1,862 years
DC <sub>avg</sub>	0 %
T <sub>M</sub> (mission time)	20 years

#### **Reduction factors**

Note	The values are reference values which may vary
St37 steel (Fe)	1
Stainless steel (V2A, 304)	Тур. 0.7
Aluminum (Al)	Тур. 0.43
Copper (Cu)	Тур. 0.3
Brass (Br)	Тур. 0.4

#### Installation note

Remark	Associated graphic see "Installation"
A	17 mm
В	34 mm
c	17 mm
D	21 mm
E	10 mm
F	56 mm
G	35 mm

#### Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714


### IQE17-07NNSKW2S | IQE

INDUCTIVE PROXIMITY SENSORS

UNSPSC 16.0901


39122230







#### **Connection diagram**

Cd-001



#### Dimensional drawing (Dimensions in mm (inch))





#### Recommended accessories

Other models and accessories → www.sick.com/IQE

	Brief description	Туре	Part no.
Plug connectors and cables			
	<ul> <li>Connection type head A: Female connector, M12, 4-pin, straight</li> <li>Description: Unshielded, Head A: female connector, M12, 4-pin, straight, unshielded, for power supply, for cable diameter 4 mm 6 mm Head B: -</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm<sup>2</sup></li> </ul>	DOS-1204-G	6007302
	<ul> <li>Connection type head A: Female connector, M12, 4-pin, angled</li> <li>Description: Unshielded, Head A: female connector, M12, 4-pin, angled, unshielded, for power supply, for cable diameter 3 mm 6.5 mm Head B: -</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm<sup>2</sup></li> </ul>	DOS-1204-W	6007303
	<ul> <li>Connection type head A: Male connector, M12, 4-pin, straight</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm<sup>2</sup></li> </ul>	STE-1204-G	6009932
	<ul> <li>Connection type head A: Male connector, M12, 4-pin, angled</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm<sup>2</sup></li> </ul>	STE-1204-W	6022084

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

