

PRODUCT-DETAILS

MCB-10G

MCB-10G Contact Block



Informations générales

Extension du type de produit	MCB-10G
Code de produit	1SFA611610R1101
EAN	7320500544372
Description courte	MCB-10G Contact Block

Description longue	<p>The MCB-10G Contact Block is: - Non-illuminated - Gold plated contact block - Front mounting - silver gold plated (Ag/Au) - 1 NO - 0NC - 690 V</p> <p>This Contact Block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.</p>
--------------------	---

Commande

Quantité minimum	10 pièce
Code douanier	8536901000

Downloads Préférés

Fiche produit, informations techniques	1SFC151007C02__
Instructions et manuels	1SFC151011M0201

Dimensions

Produit Largeur Net	0.01 m
Produit Hauteur Net	0.044 m
Produit Longueur Net	0.028 m
Poids net	0.04 kg

Technique

Température de l'air ambiant	Operation -25 ... +70 °C Storage -40 ... +85 °C
Voyant	Non-illuminated
Fonction	Without holder
Type de montage	Front mounting
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Indice de protection	Terminals IP20
Degré de pollution	3
Tension assignée d'isolement (U _i)	690 V
Tension assignée de tenue aux chocs (U _{imp})	6 kV
Fréquence assignée (f)	50 / 60 Hz
Tension	Maximum 690 V
Courant assignée d'emploi DC-13 (I _e)	(24 V) 5 A (125 V) 0.55 A
Courant assignée d'emploi AC-15 (I _e)	(230 V AC) 6 A
Power Loss	Maximum 2.5 W
Durabilite mecanique	10 million
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.9 N·m
Wire Stripping Length	8 mm
Adapté pour	MP1 MP2 MP3 MP4 MPD1 MPD2 MPD3 MPD4 MPD5 MPD11 MPD12 MPD13 MPD14 MPD15 MPD16 MPM1 MPM2

KP6
 MPET3
 MPEP3
 MPEK3
 MPET4
 MPEP4
 MPEK4
 MPMT3
 MPMT4
 MPMP3
 MPMP4
 M2SS1
 M2SS2
 M2SS3
 M2SS4
 M2SS5
 M2SS6
 M3SS1
 M3SS2
 M3SS3
 M3SS4
 M3SS5
 M3SS6
 M3SS7
 M3SS8
 M3SSC1
 M3SSC2
 M3SSC3
 M3SSC4
 M3SSC5
 M3SSC6
 M3SSC7
 M3SSC8
 M2SSK1
 M2SSK2
 M2SSK3
 M3SSK1
 M3SSK2
 M3SSK3
 MTS1
 MTS2
 MTS3
 MJS1
 MJS2
 MJS5
 MJS6
 MJS7
 MJS8
 MJS11
 MJS12

Adapté pour la classe de produit	Pilot Devices
----------------------------------	---------------

Technique UL/CSA

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

Environnement

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
Informations RoHS	2CMT2015-005452
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

Certificats et Déclarations (Numéro de document)

CB Certificate	SEMKO_SE30016M2
CQC Certificate	CQC2005010304154103
Certificat ecULus	UL-E76003-20140513
Declaration of Conformity - CCC	2020980305001528
Déclaration de Conformité - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	E-14107

Emballage

Emballage Niveau 1 Unités	bag 10 pièce
Emballage Niveau 1 Largeur	0.11 m
Emballage Niveau 1 Longueur	0.15 m
Emballage Niveau 1 Hauteur	0.01 m
Emballage Niveau 1 Poids	0.4 kg
Emballage Niveau 1 EAN	7320500307793

Classifications

Code de classification d'objet	S
ETIM 6	EC000041 - bloc de contact auxiliaire
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39122221
Code de catégorie granulaire IDÉA (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2315706
E-Number (Sweden)	3714007

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Commande et signalisation

