




Product designation Product type designation			Pushbutton actuator, spring return LPCB30
General characteristics			LFCD30
Colour			Red
Type of positions			Shrouded pushbutton
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life - spring return actuators		cycles	500000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120
Weight		g	27
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature	_		
	min	°C	-25
01	max	°C	+70
Storage temperature	min	°C	40
	min max	°C	-40 +85
Dimensions	max	U	100

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1

LPCB304

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



	UL508	
Certificates		
	CCC	
	cULus	
	EAC	
	RINA	
ETIM classification		
		EC000224

ETIM 8.0

EC000221 -Front element for push button