

PRODUCT-DETAILS

SSA-F-2.1.PB.1-WL

SSA-F-2.1.PB.1-WL WL-Sens/ Sw.act. 2/1, 44



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | SSA-F-2.1.PB.1-WL |
| Code de produit | 2CKA006200A0109 |
| EAN | 4011395215982 |
| Description courte | SSA-F-2.1.PB.1-WL WL-Sens/ Sw.act. 2/1, 44 |
| Description longue | For switching 230 V \sim consumers. Communication with the free@home system is carried out wireless. With integrated switch actuator. Switching function is available also without prior programming (pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). The right sensor channel for programming additional functions (groups, scenes, etc.). For contacting 2gang rocker 6230-2x-xxx, 6231-2x-xxx, 6232-2x-xxx, 6233-2x-xxx and 6234-2x-xxx. 3 wire connection (neutral conductor required). With 230 V extension unit input (On/Off). With fixing claws. |

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|--------------------|
| Fiche produit, informations techniques | No document needed |
| Tension nominale (U_r) | 230 V |
| Voltage Range | 230 ... 230 V |
| Auxiliary Voltage AC/DC | 230 V AC/DC |

| | |
|-------------------------------------|-----------------------------------|
| Courant nominal (I_n) | 10 A |
| Maximum Switching Current | 10 A |
| Fréquence assignée (f) | 50 ... 60 Hz |
| Maximum Switching Power | 2300 W |
| Nombre de sorties | 1 |
| Maximum Number of Switching Outputs | 1 |
| Compatible Bus Systems | free@home |
| Product Range | free@home |
| Type de charge | ohmic |
| Type de montage | Flush Mounted |
| Nombre de batteries | 0 |
| Application Function | Electrical Load and Light Control |

Environnement

| | |
|---|---|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Informations RoHS | 9AKK104295D8727 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|-------------------------------------|-------|
| Produit Largeur Net | 44 mm |
| Produit Hauteur Net | 44 mm |
| Produit Longueur Net | 41 mm |
| Poids net | 99 g |
| Profondeur d'encastrement (t_2) | 32 mm |

Commande

| | |
|------------------------|-------------|
| ID du produit remplacé | 6200-0-0109 |
|------------------------|-------------|

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E3571 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001097 - Switch actuator for bus system |
| ETIM 9 | EC001097 - Switch actuator for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

| | |
|---|-------------------------|
| CN8 | 8538 90 91 |
| UNSPSC | 31251516 |
| eClass | V11.0 : 27143125 |
| Code de catégorie granulaire IDEA (IGCC) | 3268 >> Switch actuator |

Catégories

Produits basse tension → Home and Building Automation → free@home → Lighting Control → Switch Actuators 10 A

Produits basse tension → Home and Building Automation → free@home → Standard Outputs → Switch Actuators 10 A

