

PRODUCT-DETAILS

E217-16-01B220

E217-16-01B220 Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 0NO, 1NC, 0CO, EI.
Color: Grey, 1LED, White, MW:0.5



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | E217-16-01B220 |
| Code de produit | 2CCA703255R0001 |
| EAN | 7612270939183 |
| Description courte | E217-16-01B220 Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 0NO, 1NC, 0CO, EI. Color: Grey, 1LED, White, MW:0.5 |
| Description longue | Pushbutton 1 NO / 1 NC with maintenance-free LED, Rated current: 16A/250 VACPDC, LED colour: white, 115-250 VACPDC, 12-48 VACDCPDC, 110-220 VDCPDC, Module width 0,5 |

Technique

| | |
|------------------------------------|---|
| Normes et standards | EN60068-2-1 EN60068-2-2 EN60068-2-30 DIN EN 60669-1 VDE 0632-1 UL508 |
| Tension nominale (U _r) | Lamp 230 ... 250 V |
| Tension | acc. to EN 250 V AC acc. to UL 508 240 V AC |
| Voltage Range | 60 ... 220 V DC |
| Auxiliary Voltage AC/DC | LED Indicator 60...220 V AC |
| Maximum Switching Voltage | 250 V |
| Courant nominal (I _n) | 16 A |

| | |
|--|---|
| Fréquence assignée (f) | 50/60 Hz |
| Power Loss | 1.5 W |
| Puissance Watt | 1.5 W |
| Number of Contacts CO | 0 |
| Number of Contacts NC | 1 |
| Number of Contacts NO | 0 |
| Number of Main Contacts NC | 1 |
| Number of Main Contacts NO | 0 |
| Number of Auxiliary Contacts CO (SPDT) | 0 |
| Nombre de pôles | 1 |
| Nombre de LED | 1 |
| Couple de serrage | 1.2-1.5 N·m |
| Switch Type | Double Interrupting Contacts |
| Material of Conductor | Copper |
| Options Provided | 1 NC |
| Remarques | Sealable in the On and Off positions |
| Couleur | White |
| Control Element Color | Grey |
| Lamp Color | White |
| Connecting Capacity | Solid 1x1...6 mm ² Solid 2x2.5 mm ² Flexible 1x0.75...2x2.5 mm ² |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -25...+55 °C Storage -40...+70 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CCC441014D0201 |
| REACH Declaration | 2CCC005047D0201 |
| Informations environnementales | 2CCC441003C0201 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|-------|
| Width in Number of Modular Spacings | 0.5 |
| Produit Largeur Net | 9 mm |
| Produit Hauteur Net | 85 mm |
| Produit Longueur Net | 68 mm |
| Poids net | 53 g |
| Profondeur d'encastrement (t ₂) | 75 mm |

Commande

| | |
|---------------------------|--------------|
| Emballage Niveau 1 Unités | box 10 pièce |
|---------------------------|--------------|

| | |
|--------------------------|-----------|
| Emballage Niveau 1 Poids | 594 g |
| E-Number (Finland) | 2312316 |
| E-Number (Switzerland) | 467573018 |

Certificats et Déclarations (Numéro de document)

| | |
|-------------------------------------|-----------------|
| CB Certificate | 9AKK108466A3845 |
| CCC Certificate | 9AKK108466A3829 |
| Déclaration de Conformité - CE | 2CCC441014D0201 |
| Declaration of Conformity - UKCA | 9AKK108467A6137 |
| EAC Certificate | 9AKK107991A4779 |
| VDE Certificate | 9AKK107991A9822 |

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CCC441003C0101 |
|--|-----------------|

Classifications

| | |
|--------------------------------|--|
| ETIM 8 | EC001546 - Push button for distribution board |
| ETIM 9 | EC001546 - Push button for distribution board |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85365053 |
| eClass | V11.0 : 27142302 |
| Code de classification d'objet | S |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

