

PRODUCT-DETAILS

# OT200E04P

## OT200E04P SWITCH-DISCONNECTOR



### Informations générales

Extension du type de produit	OT200E04P
Code de produit	1SCA022713R4930
EAN	6417019228747
Description courte	OT200E04P SWITCH-DISCONNECTOR
Description longue	4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

### Valeur Circulaire

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Instructions relatives à la fin de vie	1SCC301117M0201
Informations environnementales	1SCC301265D0201
Environmental Product Declaration - EPD	1SCC301282D0201
REACH Declaration	1SCC011021D0201
Informations RoHS	1SCC011020D0201
Toxic Substances Control	1SCC011025D0201

Act - TSCA

---

## Eco Transparence

---

Environmental Product Declaration - EPD	1SCC301282D0201
---	-----------------

---



---

## Commande

---

Quantité minimum	1 pièce
Code douanier	85365080
Pays d'origine	Finland (FI)

---



---

## Downloads Préférés

---

Fiche produit, informations techniques	1SCC301020C0201
Instructions et manuels	1SCC301031M0220
Mechanical Drawings	1SCC301392F0001 1SCC301201F0001 OT200-250E04.igs
Environmental Product Declaration - EPD	1SCC301282D0201
Instructions relatives à la fin de vie	1SCC301117M0201

---



---

## Dimensions

---

Produit Largeur Net	180.5 mm
Produit Hauteur Net	150 mm
Produit Longueur Net	82.5 mm
Poids net	1.8 kg

---



---

## Technique

---

Rated Operational Current AC-21A ( $I_g$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A (1000 V) 200 A
Rated Operational Current AC-22A ( $I_g$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A ( $I_g$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Power AC-23A ( $P_g$ )	(220 ... 240 V) 60 kW (400 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Courant thermique conventionnel à l'air libre ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 200 A

---

Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 200 A
Tension assignée de tenue aux chocs ( $U_{imp}$ )	12 kV
Tension assignée d'isolement ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Tension	Circuit principal 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 30 kA
Courant assigné de courte durée admissible ( $I_{cw}$ )	for 1 s 8 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(315 A fuse, 500 V) 100 kA (355 A fuse, 690 V) 80 kA (250 A fuse, 690 V) 100 kA
Power Loss	at Rated Operating Conditions per Pole 4.0 W
Degré de pollution	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Mode de fonctionnement	Front operated
Normes et standards	IEC 60947-3
Fonctions spéciales	No
Type de montage	Base mounting
Nombre de pôles	4
Indice de protection	Front IP00
Type de borne	Lug terminals
Terminal Width	20 mm
Couple de serrage	acc. IEC 60947-1 15 ... 22 N·m
Durabilité mécanique	20000
Lock Type	Yes

---

## Technique UL/CSA

---

Couple de serrage	acc. IEC 60947-1 15 ... 22 N·m
-------------------	--------------------------------

---



---

## Environnement

---

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations environnementales	1SCC301265D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

---

---

**Certificats et Déclarations (Numéro de document)**


---

Certificat ATEX	No certification needed
Certificat BV	1SCC301103D0201
Déclaration de Conformité - CE	1SCC301131D2705
DNV GL Certificate	1SCC301174D0204
Certificat GL	1SCC301139D0201
Certificat LR	1SCC301144D0201
REACH Declaration	1SCC011021D0201
Certificat UL	No certification needed
VDE Certificate	No certification needed

---



---

**Emballage**


---

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	170 mm 6.69 in
Emballage Niveau 1 Longueur	190 mm 7.48 in
Emballage Niveau 1 Hauteur	145 mm 5.71 in
Emballage Niveau 1 Poids	2.1 kg 0.93 lb
Emballage Niveau 1 EAN	6417019228747

---



---

**Classifications**


---

Code de classification d'objet	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3661306
E-Number (Sweden)	3171157

---



---

**Catégories**


---

Produits basse tension → Interrupteurs → Interrupteurs-sectionneurs

