

PRODUCT-DETAILS

AF40-22-00-14

AF40-22-00-14 250-500V50/60HZ-DC Contactor



Informations générales

Extension du type de produit	AF40-22-00-14
Code de produit	1SBL347501R1400
EAN	3471523133846
Description courte	AF40-22-00-14 250-500V50/60HZ-DC Contactor

Description longue	<p>The AF40-22-00-14 is a 4 pole - 690 V IEC or 600 UL contactor with screw terminals, controlling motors up to 18.5 kW / 400 V AC (AC-3) and switching power circuits up to 70 A (AC-1) or 60 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (250-500 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
--------------------	---

Commande

Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Instructions et manuels	1SBC101047M6801
-------------------------	-----------------

CAD Dimensional
Drawing

2CDC001079B0201

Dimensions

Produit Largeur Net	70 mm
Produit Longueur Net	113.5 mm
Produit Hauteur Net	125.5 mm
Poids net	1.16 kg

Technique

Number of Main Contacts NO	2
Number of Main Contacts NC	2
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Normes et standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Tension	Circuit principal 690 V
Fréquence assignée (f)	Circuit de commande 50 / 60 Hz Circuit principal 50 / 60 Hz
Courant thermique conventionnel à l'air libre (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 105 A
Courant assignée d' emploi AC-1 (I_e)	(690 V) 40 °C 70 A (690 V) 60 °C 60 A (690 V) 70 °C 50 A
Courant assignée d' emploi AC-3 (I_e)	(415 V) 60 °C 40 A (440 V) 60 °C 40 A (500 V) 60 °C 35 A (690 V) 60 °C 25 A (380 / 400 V) 60 °C 40 A (220 / 230 / 240 V) 60 °C 40 A
Puissance assignée d' emploi AC-3 (P_e)	(415 V) 22 kW (440 V) 22 kW (500 V) 22 kW (690 V) 22 kW (380 / 400 V) 18.5 kW (220 / 230 / 240 V) 11 kW
Courant assigné de courte durée admissible (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 690 V 600 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour
Tension assignée d' isolement (U_i)	acc. to IEC 60947-4-1 690 V acc. to UL/CSA 600 V
Tension assignée de	6 kV

tenue aux chocs (U_{imp})

Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 250 ... 500 V 60 Hz 250 ... 500 V DC Operation 250 ... 500 V
Coil Consumption	Average Holding Value 50 / 60 Hz 4 V·A Average Holding Value 50 Hz 4 V·A Average Holding Value 60 Hz 4 V·A Average Holding Value DC 2 W Average Holding Value, from Warm State 2 W
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 or 2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 4 ... 35 mm ² Flexible with Insulated Ferrule 1/2x 4 ... 35 mm ² Rigid Stranded 1/2x 6 ... 35 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Control Circuit 10 mm Main Circuit 16 mm
Indice de protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Type de borne	Screw Terminals

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Circuit principal 600 V
General Use Rating UL/CSA	(600 V AC) 60 A
Connecting Capacity Main Circuit UL/CSA	Rigid Stranded 1/2x 10-2 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Control Circuit 11 in·lb Main Circuit 35 in·lb

Environnement

Température de l'air ambiant	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Altitude de fonctionnement maximale autorisée	Without Derating 3000 m
REACH Declaration	2CMT2021-006202
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 3 g Closed position / 2 g Open position
Informations RoHS	2CMT2021-006277
Statut RoHS	Following EU Directive 2011/65/EU

Certificats et Déclarations (Numéro de document)

Certificat ABS	ABS_20-2060694-PDA
Certificat BV	BV_2634H36994B1
CB Certificate	CB_SE-108889A1M1
CCC Certificate	CCC_2015010304824714
CQC Certificate	CQC2015010304824714
Declaration of Conformity - CCC	2020980304001256
Déclaration de Conformité - CE	1SBD250001U1000
Declaration of Conformity - UKCA	1SBD250032U1000
Certificat DNV	DNV_TAE00001AF-4
EAC Certificate	EAC_RU_FRME77B03447
KC Certificate	KC_HW02016-15009C
Certificat UL	UL-US-L312527-1142-02114102-6 UL-CA-L312527-4142-02114102-6
UL Listing Card	UL_E312527

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	150 mm
Emballage Niveau 1 Longueur	150 mm
Emballage Niveau 1 Hauteur	103 mm
Emballage Niveau 1 Poids	1.27 kg
Emballage Niveau 1 EAN	3471523133846
Emballage Niveau 2 Unités	box 8 pièce
Emballage Niveau 2 Largeur	250 mm
Emballage Niveau 2 Longueur	300 mm
Emballage Niveau 2 Hauteur	300 mm
Emballage Niveau 2 Poids	10.16 kg
Emballage Niveau 3 Unités	192 pièce

Classifications

Code de classification d'objet	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching

ETIM 6	EC000066 - contacteur de puissance pour commutation de courant alternatif
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
Code de catégorie granulaire IDEA (IGCC)	4758 >> Iec Contactors
E-Number (Finland)	3707556
E-Number (Sweden)	3210308

