

PRODUCT-DETAILS

CR-S024VDC1TRI

CR-S024VDC1TRI Pluggable optocoupler Input= 24 V DC, Output= 2 A/240 V AC



Informations générales

Extension du type de produit	CR-S024VDC1TRI
Code de produit	1SVR405510R3070
EAN	4013614486630
Description courte	CR-S024VDC1TRI Pluggable optocoupler Input= 24 V DC, Output= 2 A/240 V AC
Description longue	The CR-S024VDC1TRI slim pluggable optocoupler with Triac output is suitable for direct mounting on a printed circuit board or use in conjunction with ABB's CR-S sockets. This relay operates with a 240 V AC rated control supply voltage and has a maximum switching voltage of 275 V AC and maximum switching current of 2 A. Coupled with a socket, the compact size of this relay offers possibilities to save space within a control panel. CR-S screw and spring sockets, separator, jumper bars and marker are available as accessories.

Commande

EAN	4013614486630
Quantité minimum	10 pièce
Code douanier	85369095

Downloads Préférés

Fiche produit, informations techniques	2CDC110004C0210_05
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	15 mm
Produit Hauteur Net	5 mm
Produit Longueur Net	28 mm
Poids net	0.004 kg

Technique

Fonction	Pluggable slim optocoupler CR-S
Rated Control Supply Voltage (U _s)	24 V DC
Sortie	TRIAC
Output Signal	240VAC / 2A
Indice de protection	IP00
Normes et standards	IEC/EN 61000-6-2 IEC/EN 61000-6-3

Environnement

Informations RoHS	1SVD981001-4400
Statut RoHS	Following EU Directive 2011/65/EU

Certificats et Déclarations (Numéro de document)

cUR Certificate	cUR_E244330
Déclaration de Conformité - CE	1SVD982057-0000
EAC Certificate	EAC_RU_C-DE.ME77.B.00443-19
UR Certificate	UR_E244330

Emballage

Emballage Niveau 1 Unités	box 10 pièce
Emballage Niveau 1 Largeur	23.7 mm
Emballage Niveau 1 Longueur	7.4 mm
Emballage Niveau 1 Hauteur	300 mm
Emballage Niveau 1 Poids	0.05 kg
Emballage Niveau 1 EAN	4013614509216

Classifications

ETIM 7	EC001504 - Optocoupler
ETIM 8	EC001504 - Optocoupler
ETIM 9	EC001504 - Optocoupler
eClass	V11.0 : 27371604
UNSPSC	32111705

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Relais et optocoupleurs d'interface

