

| | | | | | |
|--|----------------------|----------|-----|--|--|
| Product designation | | | | Rotary cam switches | |
| Product type designation | | | | GN315 | |
| General characteristics | | | | | |
| Switching diagram | | | | 69 - Changeover switch without 0 4 poles | |
| N° of elements | | | | 4 | |
| Mounting form | | | | O - Rear mounting with black handle | |
| Contact characteristics | | | | | |
| Rated insulation voltage Ui | IEC/EN | V | 690 | | |
| | UL/CSA | V | 600 | | |
| Rated impulse withstand voltage Uimp | | | kV | 8 | |
| Conventional free air thermal current Ith | IEC/EN | A | 315 | | |
| | UL/CSA | A | 255 | | |
| Rated operational voltage | | | V | 690 | |
| Rated operational impulse voltage | | | kV | 6 | |
| Maximum fuse size for short-circuit protection In (gG) | 10kA | A | 315 | | |
| | 15kA | A | 315 | | |
| Rated short time current Icw | | | 1s | A | |
| | | | | 5200 | |
| Operational current Ie IEC/EN AC1/AC21A | | | A | 315 | |
| | | | | | |
| Rated operational power in AC Three-phase AC-3 | 220/230V | kW | 37 | | |
| | 380/440V | kW | 55 | | |
| | 500/690V | kW | 69 | | |
| | | | | | |
| | Single-phase AC-3 | 110V | kW | 11 | |
| | | 220/230V | kW | 22 | |
| | | 380/440V | kW | 30 | |
| Rated operational current in DC DC21A | 48V | A | 200 | | |
| | 60V | A | 200 | | |
| | 110V | A | 35 | | |
| | 220V | A | 2.5 | | |
| | 440V | A | 0.9 | | |
| | | | | | |
| Power dissipation | | | W | 64.5 | |
| Mechanical features | | | | | |
| Terminals screw | | | | M10 | |
| Tightening torque for terminals max | | | Nm | 10 | |
| Conductor size | AWG - Rigid cable | | Max | AWG 1XMCM350 | |
| | AWG - Flexible cable | | | | |

| | | | |
|--|--------------------------------------|-----------------|-------------------|
| | Max | AWG | 1XMCM350 |
| Conductor size (IEC) - Flexible cable | | | |
| | Max | mm ² | 1X185 |
| Conductor size (IEC) - Rigid cable | | | |
| | Max | mm ² | 1X185 |
| Mechanical life | | cycles | 2X10 ⁵ |
| UL technical data | | | |
| Motor power for direct-on-line control | | | |
| for three-phase motor | | | |
| | 120V | HP | 30 |
| | 240V | HP | 50 |
| | 480V | HP | 100 |
| | 600V | HP | 75 |
| for single-phase motor | | | |
| | 120V | HP | 15 |
| | 240V | HP | 30 |
| Ambient conditions | | | |
| Temperature | | | |
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +55 |
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +70 |
| Resistance & Protection | | | |
| Frontal IP degree | | | IP40 |
| Terminals IP degree | | | IP00 |
| Dimensions | | | |
| Wiring diagrams | | | |
| Certifications and compliance | | | |
| Compliance | | | |
| | IEC/EN/BS 60947-1 | | |
| | IEC/EN/BS 60947-3 | | |
| | IEC/EN/BS 60947-5-1 | | |
| | UL60947-4-1 | | |
| Certificates | | | |
| | UR | | |
| ETIM classification | | | |
| ETIM 8.0 | EC001029 - Selector switch, complete | | |