



## Connection




Type	Tightening torque	Copper cables		Multi-cables	
		Rigid	Flexible	Rigid	Cables with ferrule
		DB123945	DB123007	DB123011	DB123008
Indication auxiliaries	1 N.m	1 to 4 mm <sup>2</sup>	0.5 to 2.5 mm <sup>2</sup>	2 x 2.5 mm <sup>2</sup>	2 x 1.5 mm <sup>2</sup>
Tripping auxiliaries	1 N.m	1 to 6 mm <sup>2</sup>	0.5 to 4 mm <sup>2</sup>	2 x 2.5 mm <sup>2</sup>	2 x 2.5 mm <sup>2</sup>

## Ti24 connector connection



Type	Catalogue numbers	Copper cables	
		Rigid	Flexible
		DB123945	DB123553
Ti24 interface	A9XC2412	1 x 0,5 à 1,5 mm <sup>2</sup>	1 x 0,5 à 1,5 mm <sup>2</sup>

## Ti24 prefabricated cables connection



Type	Catalogue numbers	Length
<b>Connection for Acti 9 Smartlink</b>		
6 short prefabricated	A9XCAS06	100 mm
6 medium-sized prefabricated	A9XCAM06	160 mm
6 long prefabricated	A9XCAL06	870 mm
<b>Connection for PLC type terminals</b>		
6 long prefabricated on a single side	A9XCAU06	870 mm