YM2A28-100VA6XLEAX

Sensor/actuator cable

PLUG CONNECTORS AND CABLES



YM2A28-100VA6XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES



Ordering information

Туре	Part no.
YM2A28-100VA6XLEAX	2096246

For 8-pin sensor-actuator cables, the wire colors are not standardized. Therefore, please observe the pin assignment of the sensor and the cable in the respective data sheet.

Other models and accessories -> www.sick.com/Sensor_actuator_cable



Detailed technical data

Technical specifications


Connection type head A		Male connector, M12, 8-pin, straight, A-coded
Connection type head B		Flying leads
Locking plug connector		Screw connection
Connector material		TPU
Connector color		Black
Locking nut material		Zinc die-cast, nickel-plated
Tightening torque		0.6 Nm
Width across flats		13
Cable		10 m, 8-wire, PVC
Jacket material		PVC
Jacket color		Gray
Cable diameter		7 mm
Conductor cross section		0.25 mm ²
Shielding		Shielded
Bending radius		
	Stationary position	> 10 x cable diameter
Nominal voltage, cable		300 V AC
Test voltage, cable		2,000 V AC
Reference voltage		
		30 V AC
		30 V AC 30 V DC
Rated impulse voltage		
Rated impulse voltage Current loading		30 V DC
		30 V DC 0.8 kV
Current loading		30 V DC 0.8 kV 2 A
Current loading Signal type		30 V DC 0.8 kV 2 A Sensor/actuator cable
Current loading Signal type Application		30 V DC 0.8 kV 2 A Sensor/actuator cable Zones with chemicals

YM2A28-100VA6XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES

Operating temperature	
Flexible use	-5 °C +80 °C
Stationary position	-30 °C +80 °C
Head	-25 °C +85 °C
Contamination rating	3
Insulation resistance	100 ΜΩ
Overvoltage category	III
Specific insulation resistance	30 mΩ
Thermal resistance, piping	Flame retardant according to UL 1581 VW1 / CSA FT1
Classifications	
ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



YM2A28-100VA6XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES

Recommended accessories

Other models and accessories -> www.sick.com/Sensor_actuator_cable

	Brief description	Туре	Part no.			
Other mounting accessories						
	1 piece, M12 mounting key set for SW13 with calibrated torque 0.6 Nm	TOOL-TW06M12AF13	5337208			
Plug connectors and cables						
No	 Connection type head A: Female connector, M12, 8-pin, straight Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: 0.25 mm² 0.5 mm² 	DOS-1208-G	6028422			
	 Connection type head A: Male connector, M12, 8-pin, straight Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: 0.25 mm² 0.5 mm² Note: For field bus technology 	STE-1208-G	6033269			

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

