


RANDY 4



45W
4400 lm



Corps et réflecteur aluminium. Basculant. Blanc. Alimentation 900mA, classe 2, IP20. Spot classe 3. Puissance absorbée 46,2W.

	1 LED	45W
	230V	IP20 IK02 850° 30 000 h

Faisceau	Lumens	Teinte	Code
70°	3900	3000 K	50194
70°	4400	4000 K	50193

50194	3000 K	45 W	70°
	h (m)	E_{max} (lx)	d (m)
	1	2889	1,40
	2	722	2,8
	3	321	4,2

50193	4000 K	45 W	70°
	h (m)	E_{max} (lx)	d (m)
	1	3300	1,40
	2	825	2,8
	3	367	4,2




HCD



Corps aluminium blanc/Verre trempé. Basculant.

	HIT-TC-CE (MT)
	230V IP20 IK02 850°
Spot	P (w) Douille Code sans lampe
HCD 70	35/70 G8,5 0934

KIT HCD 70



P (w)	Spot	Type Platine	Platine	Lampe	Teinte	Code
35	0934	électronique	0680	2706	3000 K	1487
70	0934	électronique	0690	2707	3000 K	1488

Code : 1487	35 w	50°	
	h (m)	E (lx)	d (m)
	1	1040	0,94
	2	260	1,9
	2,5	166	2,4

Code : 1488	70 w	50°	
	h (m)	E (lx)	d (m)
	1	2120	0,94
	2	530	1,9
	2,5	339	2,4

