

PRODUCT-DETAILS

# CM-TCS.22P

## CM-TCS.22P Temperature monitoring relay Temp.-range 0...+100°C, 24VAC/DC



### Informations générales

Extension du type de produit	CM-TCS.22P
Code de produit	1SVR740740R9200
EAN	4016779852814
Description courte	CM-TCS.22P Temperature monitoring relay Temp.-range 0...+100°C, 24VAC/DC
Description longue	The CM-TCS.22P relay is from the CM temperature monitors range. This relay operates with a rated control supply voltage of 24 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. The CM-TCS.22P is able to measure temperature with 1 sensor circuit using PT100 sensor. The CM-TCS.22P monitors overtemperature, undertemperature and window monitoring with 2 thresholds. The corresponding threshold values are adjustable. The temperature measuring range is 0...+100°C. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

### Commande

EAN	4016779852814
Quantité minimum	1 pièce
Code douanier	85364900

### Downloads Préférés

Fiche produit, informations techniques	2CDC112199D0201
Instructions et manuels	1SVC730560M1001

1SVC730560M0001

CAD Dimensional  
Drawing

2CDC001079B0201

## Dimensions

Produit Largeur Net	22.5 mm
Produit Hauteur Net	85.6 mm
Produit Longueur Net	103.7 mm
Poids net	0.127 kg

## Technique

Fonction	Overtemperature monitoring Undertemperature monitoring Over- and undertemperature monitoring
Plage de mesure	0 ... +100 °C
Sensor Type	PT100
Rated Control Supply Voltage ( $U_s$ )	24 V AC/DC
Fréquence assignée (f)	Supply Circuit 50 Hz Supply Circuit 60 Hz Supply Circuit DC
Sortie	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Type de borne	Screwless Terminals
Rated Operational Current AC-12 ( $I_e$ )	(230 V) 4 A
Courant assignée d'emploi AC-15 ( $I_e$ )	(230 V) 3 A
Rated Operational Current DC-12 ( $I_e$ )	(24 V) 4 A
Courant assignée d'emploi DC-13 ( $I_e$ )	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Tension assignée de tenue aux chocs ( $U_{imp}$ )	Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
Tension assignée d'isolement ( $U_i$ )	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Indice de protection	Housing IP50 Terminals IP20
Catégorie de Surtension	III
Degré de pollution	3
Dispositif de protection contre les courts-circuits	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Durabilite mecanique	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible 2x 0.5 ... 1.5 mm <sup>2</sup> Rigid 2x 0.5 ... 1.5 mm <sup>2</sup>
Wire Stripping Length	8 mm
Type d'encastrement	1 ... 6
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

## Normes et standards

CAN/CSA C22.2 No.60947-5-1  
 IEC/EN 60255-26  
 IEC/EN 60255-27  
 IEC/EN 61000-6-2  
 IEC/EN 61000-6-3  
 IEC/EN 63000  
 UL 60947-5-1  
 IEC/EN 60947-5-1

---

**Technique UL/CSA**


---

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300

---

**Environnement**


---

Température de l'air ambiant	Operation -40 ... +60 °C Storage -40 ... +85 °C
Altitude de fonctionnement maximale autorisée	Without Derating 2000 m
REACH Declaration	1SVD981001-4501
Informations RoHS	1SVD981015-00
Statut RoHS	Following EU Directive 2011/65/EU

---

**Valeur Circulaire**


---

Instructions relatives à la fin de vie	1SAC200290H0001
--	-----------------

---

**Certificats et Déclarations (Numéro de document)**


---

CCC Certificate	CCC_2018010303056014
CQC Certificate	CQC2007010303243843
Certificat ecULus	cULus60947-5-1_20170922-E140448
Declaration of Conformity - CCC	2020980303000196
Déclaration de Conformité - CE	1SVD981015-00
Declaration of Conformity - UKCA	1SVD981015-10
DNV GL Certificate	DNV_GL_TAA000021M
EAC Certificate	EAC_RU_C-DE.ME77.B.03424

---

**Emballage**


---

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	97 mm
Emballage Niveau 1 Longueur	30 mm
Emballage Niveau 1	109 mm

Hauteur

Emballage Niveau 1 Poids 0.152 kg

Emballage Niveau 1 EAN 4016779852814

---

## Classifications

Code de classification d'objet	B
ETIM 7	EC001446 - Temperature monitoring relay
ETIM 8	EC001446 - Temperature monitoring relay
ETIM 9	EC001446 - Temperature monitoring relay
eClass	V11.0 : 27371810
UNSPSC	39122331
E-Number (Finland)	2712329
E-Number (Sweden)	3860673

---

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Contrôle des températures

