

Features

Use: Indoor
 Type of installation: SUSPENDED, CEILING MOUNTED
 Emission: DIRECT
 Optics: BATWING
 Colour: WHITE
 Dimming: ON/OFF
 Emergency: Autonomy 1h/Recharge time 12h
 L: 1693mm
 A: 60mm
 H: 80mm
 Made in: ITALY
 Warranty: 5 years except battery
 Weight: 6kg

Tech data

Luminaire input power: 55.8W
 Luminaire luminous flux: 6254lm
 Luminous flux in emergency: 10%
 IP: 40
 Insulation class: I
 Supply voltage: 220-240V 50/60Hz
 SELV: No

Source

Light source: LED
 Source power: 50W
 Source luminous flux: 6801lm
 Colour temperature: 4000K
 CRI: >90
 Colour tolerance: 3 Step MacAdam
 LED lifespan: 50000h L80 B10

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-22

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

MOUNTING ACCESSORIES




HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



KIT ALIMENTAZIONE L3000 3P BIA

108920.01