

PRODUCT-DETAILS

# N2241 AN

## 110° motion sensor - 2M - Anthracite Movement sensor Anthracite - Zenit



### Informations générales

Extension du type de produit	N2241 AN
Code de produit	2CLA224100N1801
EAN	8427238074726
Description courte	110° motion sensor - 2M - Anthracite Movement sensor Anthracite - Zenit

Description longue	Color: Anthracite. Rated voltage: 127 - 230 Vac ± 10% / 50 - 60 Hz Outputs: 1 Normally Open (NO). Potential free Max. power: - Incandescent: 1.800W @230Vac / 1.000W @127Vac - Halogen with electronic or ferromagnetic transformer: 750VA @230Vac / 400VA @127Vac - Fluorescent lamps or motors: 400VA @230Vac / 200VA @127Vac For automatic switching of devices dependent on motion and brightness. With integrated selector switch for ON-AUTOMATIC-OFF in the front side. Switch-off delay: 10 sec to 10 min or short-time pulse 1 sec adjustable (from the front side). Detection range: 5 m radius Adjustable light set point level for activation (from the front side). Detection angle: 110 ° Mounting height: 1,2 m Auxiliary control with N2X04.X push-buttons Temperature range (Device): -10 °C to 40 °C Size: 2 modules.
--------------------	---

### Installation

Instructions et manuels	2CLX224109N1001
-------------------------	-----------------

## Technique

Fiche produit, informations techniques	9AKK10103A5108
Tension nominale (U <sub>r</sub> )	230 V
Type de tension	AC
Current Range	Minimum 3 A Maximum 8 A
Maximum Control Current DC	1800 mA
Fréquence (f)	50...60 Hz
Maximum Switching Power	1800 W
Plage de mesure	Diameter Detection range on floor 5 m
Number of Switching Zones	3
Design Range	Zenit
Délai (T)	On 10 second [unit of time] Off 600 second [unit of time]
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de raccordement	Screw
Type de montage	Flush Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Decor Surface finishing: Matt
Matériau	Material quality: Thermoplastic Material: Plastic
Flux lumineux	3...1000 lx
Model Number	Movement sensor
RAL Number	RAL 9010 - Blanc pur
Couleur	Anthracite
Nombre de batteries	0
Application Function	Electrical Load and Light Control

## Environnement

Température de l'air ambiant	Operation -5 ... +35 °C Storage -5 ... +50 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CLC224100N1801
REACH Declaration	9AKK108467A7464
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Produit Largeur Net	44 mm
Produit Hauteur Net	44 mm
Produit Longueur Net	40 mm
Poids net	0.079 kg
Profondeur d'encastrement (t <sub>2</sub> )	32 mm

---

## Commande

---

ID du produit remplacé	2CLA224100N1802 2CLA224100N1803
------------------------	------------------------------------

---



---

## Certificats et Déclarations (Numéro de document)

---

Déclaration de Conformité - CE	9AKK106930A2195
-----------------------------------	-----------------

---



---

## Classifications

---

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365080

---



---

## Catégories

---

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls



360