



E2S22D - factory ref  
O50F - commercial ref

E2S22DBZ - factory ref  
O50BE - commercial ref

E2S22DFS - factory ref  
O50C - commercial ref

E2S22DBF - factory ref  
O50B - commercial ref



**Pilot Light:**

**Red**

E2S22D12VR	12V ac/dc <80mA	12-chips Super-Bright
E2S22D24VR	24V ac/dc <80mA	12-chips Super-Bright
E2S22D48VR	48V ac/dc <20mA	12-chips Super-Bright
E2S22D130VR	110-130V ac/dc 25mA Max	12-chips Super-Bright
E2S22D230VR	230V ac 25mA Max	12-chips Super-Bright



**Pilot Light:**

**Amber**

E2S22D12VA	12V ac/dc <80mA	12-chips Super-Bright
E2S22D24VA	24V ac/dc <80mA	12-chips Super-Bright
E2S22D48VA	48V ac/dc <20mA	12-chips Super-Bright
E2S22D130VA	110-130V ac/dc 25mA Max	12-chips Super-Bright
E2S22D230VA	230V ac 25mA Max	12-chips Super-Bright



**Pilot Light:**

**Green**

E2S22D12VG	12V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D24VG	24V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D48VG	48V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D130VG	110-130V ac/dc 25mA Max	1-chip InGAN Ultra Super-Bright
E2S22D230VG	230V ac 25mA Max	1-chip InGAN Ultra Super-Bright



**Pilot Light:**

**Blue**

E2S22D12VB	12V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D24VB	24V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D48VB	48V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D130VB	110-130V ac/dc 25mA Max	2-chip InGAN Ultra Super-Bright
E2S22D230VB	230V ac 25mA Max	2-chip InGAN Ultra Super-Bright



**Pilot Light:**

**White**

E2S22D12VW	12V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D24VW	24V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D48VW	48V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D130VW	110-130V ac/dc 25mA Max	1-chip InGAN Ultra Super-Bright
E2S22D230VW	230V ac 25mA Max	1-chip InGAN Ultra Super-Bright



## O50BE

### Buzzer:

E2S22DBZ  
80 db at 10cm;  
Current : 15-30mA;

## O50C

### Flashing pilot light:

E2S22DFS  
Flash Rate: 2Hz;  
Current : 15-30mA;

## O50B

### Combination:

E2S22DBF  
80 db at 10 cm;  
Current : 18-80mA;

## O50F

### Pilot lights:

E2S22D  
Low voltage DC/AC:  
Current : 20-80mA;  
High voltage DC/AC:  
Current : 18-25mA;

### Buzzer:

E2S22DBZ24V  
E2S22DBZ48V  
E2S22DBZ130V  
E2S22DBZ230V

### 80dB @ 10cm Current: 15-30mA

24V dc/ac Buzzer  
48V dc/ac Buzzer  
110-130V ac/dc Buzzer  
230V ac Buzzer

### Flashing Pilot Light:

E2S22DFS24V  
E2S22DFS48V  
E2S22DFS130V  
E2S22DFS230V

### Flash rate: 2Hz Current: 15-30mA

24V ac/dc 2x LED Red  
48V ac/dc 2x LED Red  
110-130V ac/dc 2x LED Red  
230V ac 2x LED Red

### Combination:

E2S22DBF24V  
E2S22DBF48V  
E2S22DBF130V  
E2S22DBF230V

### 80dB @ 10cm With Red LED

24V ac/dc Buzzer & 2x LED Red lo: 20-80mA  
48V ac/dc Buzzer & 2x LED Red lo: 20-80mA  
110-130V ac/dc Buzzer & 2x LED Red lo: 18-30mA  
230V ac Buzzer & 2x LED Red lo: 18-30mA

### E2S22DMT

E2S22DLBHF25X18  
E2S22DLBHF25X10

### Mounting Tool for E2S-22D LED Pilot Lights

E2S-22D Label holder 25x18mm  
E2S-22D Label holder 25x10mm

