



**CARACTERISTIQUES ELECTRIQUES
ELECTRICAL CHARACTERISTICS**

Type		Rechargeable Nickel Metal Hydride
IEC Designation		AAA
Plot / Top		Flat top
Tension nominale / Nominal voltage		1.2V
Tension mini en décharge / Mini discharge voltage		1V
Charge standard 16h		80 mA
Capacité nominale / Nominal Capacity		800 mAh
Capacité mini / Minimal Capacity		750 mAh
Cycle life at 80% DOD (0,5C)		> 500 (IEC standard)
Resistance Interne / Internal Impedance (at 1000hz)		< 65 Ω hms
Température d'usage / Ambient temperature	Charge / Charging	0 to 45 °c
	Décharge / Discharging	-20 to 60 °c
Temperature de stockage / Storage temperature		-20 to 45 °c (Humidity: 65 \pm 20 %)
Charge rapide / Fast charge		800mA - $\Delta V=0.5mV/Cell$
Charge de maintient / Trickle charge		(0.05C)~(0.1C)

**CARACTERISTIQUES PHYSIQUES
PHYSICAL CHARACTERISTICS**

Accumulateur / Battery	
Dimension (mm)	44 x 10.5 (+/- 1)
Poids / Weight (g.)	12

