

PRODUCT-DETAILS

A41 113-100

A41 113-100, Energy meter'Steel', M-bus, Single-phase, 80 A



Informations générales

Extension du type de produit	A41 113-100
Code de produit	2CMA100240R1000
ABB désignation de type	A41 113-100
EAN	7392696002400
Description courte	A41 113-100, Energy meter'Steel', M-bus, Single-phase, 80 A

Description longue	Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected for active energy. One output for pulses or alarm etc. M-Bus communication. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.
--------------------	--

Eco Transparence

Environmental Product Declaration - EPD	9AKK108467A4138
---	-----------------

Technique

Normes et standards	IEC 62052-11, IEC 62053-21, EN 50470-1, EN 50470-3
Fonction	Electricity meter
Sub-Function	Steel
	57.7-288 V

Tension nominale (U _r)	
Courant nominal (I _n)	5 A Maximum 80 A
Intensité de courant	80 A
Fréquence assignée (f)	50 / 60 Hz
	0.807 W
Interface de communication	M-bus
Précision	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Rating	One-Tariff
Pulse Output Rate	1-999999
Nombre de pôles	1
Nombre de phases	Single-phase
Number of Counter Positions	7
Nombre d'entrées/sorties numériques	1 DO
Meter Type	Direct connected
Type de montage	DIN-Rail
Pulse Output Type	Electrical
Type d'affichage	Digital
Matériau du boîtier	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Connecting Capacity Main Circuit	1 ... 25 mm ²

Environnement

Température de l'air ambiant	Operation -40 ... 70 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	2CMC484006
Informations environnementales	2CMC484004D0001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	4
Produit Largeur Net	70 mm
Produit Hauteur Net	26.5 mm
Produit Longueur Net	65 mm
Poids net	0.246 kg
Taille	97X70X65

Commande

Emballage Niveau 1 Unités	box 1 pièce
---------------------------	-------------

Emballage Niveau 1 Poids	0.318 kg
E-Number (Finland)	6625052
E-Number (Sweden)	0900061

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CMC484003D0001
-----------------------------------	-----------------

Installation

Instructions et manuels	2CMC484004M0201
-------------------------	-----------------

Downloads Préférés

Fiche produit, informations techniques	2CMC484002M0201
---	-----------------

Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283011
eClass	V11.0 : 27142316
Code de classification d'objet	P

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Compteurs d'énergie → Compteurs d'énergie

