


**ENERGY AND AUTOMATION** 



Product designation			Illuminated button actuators, spring return - Extended
Product type designation  General characteristics			LPCBL20
Colour			Blue
Coloui			Extended
Type of positions			pushbutton
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life - spring return actuators		cycles	5000000
Mounting adapter			LPXAU120
Weight		g	27
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85
Dimensions			



## Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

## Certificates



## LPCBL206

electric ILLUMINATED BUTTON ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES CHROMED PLASTIC, EXTENDED, BLUE

CCC		
cULus		
EAC		
RINA		

ETIM classification

ETIM 8.0

EC000221 -Front element for push button