

# Presslok™ Splice Connectors UB2A, Jar



**Part Number:  
UB2A-JAR**

With the Presslok™ series of tools and connectors, service providers can meet the demand for enhanced customer services such as high-speed internet, video-on-demand, and video conferencing. Presslok connectors also offer full wire-range capability, increased port size to accommodate up to 2.08 mm (0.082 in) insulation sizes, and solvent resistant plastic construction. As new technologies migrate into the local loop, the importance of reliable connections in the embedded plant has increased exponentially. Each connection is a potential point of failure in high-bandwidth applications, which could require additional time and expense for a technician to repair. That is where the full line of Presslok connectors can really make a difference.

## Features and Benefits

Fast installation

---

Ease of Use

---

Wide Range of Common Wire Guages

---

Factory-installed sealant

---

Dry versions available for Central Offices and Vaults



Presslok™ Splice Connectors, UB2A Gel-filled IDC Tap Splice Connector, Jar Packaging (500 pce)

# Presslok™ Splice Connectors UB2A, Jar



## Specifications

### General Specifications

Product type	Copper Splice Connector
--------------	-------------------------

### Design

Composition	Gel-filled
No. of connections	Two (2)
Connector type	Tap
Conductor	AWG 26 - 19
Conductor Range	0.4 mm to 0.9 mm

### Ordering Information

Product Number	UB2A-JAR
EAN Code	4059496710852
Packaging method	Jar
Units per delivery	5000/1



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2023 Corning Optical Communications. All rights reserved.