

1SNA400772R1300 ✓ ACTIVE

ENTRELEC | ENTRELEC SNA

TE Internal #: 1SNA400772R1300

Modular Terminal Blocks, Ground, Screw Clamp Terminal Block,
Green & Yellow, Product Spacing .865 in [22 mm], 6 Position, Screw
Terminal, ENTRELEC SNA

[View on TE.com >](#)



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Ground**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Rated Cross Section: **70 mm²**

Primary Product Color: **Green & Yellow**

Features

Product Type Features

| | |
|-------------------------------------|----------------------------|
| Modular Terminal Block Product Type | Screw Clamp Terminal Block |
|-------------------------------------|----------------------------|

Configuration Features

| | |
|---------------------|--------|
| Gauge Type | B11 |
| Number of Levels | 1 |
| Number of Poles | 2 |
| Number of Circuits | 1 |
| Block Function | Ground |
| Number of Positions | 6 |

Electrical Characteristics

| | |
|---|--------|
| Impulse Withstanding Voltage Rating (IEC) | 8000 V |
| Dielectric Test Voltage | 2200 V |
| Short-Time Withstanding Current Rating @ 1s | 8400 A |

Body Features

| | |
|-----------------------|----------------|
| Product Weight | 222 g |
| Primary Product Color | Green & Yellow |

Termination Features

| | |
|------------------------------------|----------------|
| Termination Method to Wire & Cable | Screw Terminal |
|------------------------------------|----------------|

Mechanical Attachment

| | |
|-------------------------|-----------|
| DIN Rail Mounting Type | TH35-15 |
| Tightening Torque | 52 in-lbs |
| Connector Mounting Type | DIN Rail |

Housing Features

| | |
|------------------|---------------|
| Housing Material | Polyamide 6.6 |
|------------------|---------------|

Dimensions

| | |
|--|-------------------------|
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp | 4 – 00 AWG |
| Wire Stripping Length | 25 mm [.984 in] |
| Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp | 16 – 70 mm ² |
| Tool Size | 6 mm [.236 in] |
| Product Depth | 68.8 mm |
| Product Width | 22 mm [.865 in] |
| Product Length | 68.8 mm |
| Product Height | 74 mm |
| Rated Cross Section | 70 mm ² |
| Product Spacing | 22 mm [.865 in] |
| Wire Size | 70 mm ² |

Usage Conditions

| | |
|--------------------------------|-----------------------------|
| Storage Temperature Range | -55 – 110 °C [-67 – 230 °F] |
| Installation Temperature Range | -5 – 40 °C [23 – 104 °F] |
| Operating Temperature Range | -55 – 110 °C [-67 – 230 °F] |

Operation/Application

| | |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

Industry Standards

| | |
|------------------------|----------|
| IP Rating | IP10 |
| UL Flammability Rating | UL 94V-0 |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|------------------------------|-----------|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |



| | |
|---|---|
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1SNA238000R1600
RC1010

TE Part # 1SNA116900R2700
BADH




Also in the Series | ENTRELEC SNA

Modular Terminal Blocks(182)

Terminal Block & Strip Conducting Accessories(26)

Terminal Block & Strip Insulating Accessories(14)

Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNA400772R1300_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA400772R1300_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA400772R1300_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Catalogue - ENTRELEC terminal-blocks-sna-series](#)

English

[D70/22.P](#)

English

1SNA400772R1300

Modular Terminal Blocks, Ground, Screw Clamp Terminal Block, Green & Yellow,
Product Spacing .865 in [22 mm], 6 Position, Screw Terminal, ENTRELEC SNA



ENTRELEC Terminal Blocks Catalogue (RUS)