

PRODUCT-DETAILS

CL2-523Y

CL2-523Y Pilot Light



Informations générales

Extension du type de produit	CL2-523Y
Code de produit	1SFA619403R5233
EAN	7320500556412
Description courte	CL2-523Y Pilot Light
Description longue	The CL2-523Y Pilot Light is: Compact - Pilot Light - Pilot light head - Yellow - Illuminated - 230V AC This Pilot Light is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance.

Commande

Quantité minimum	10 pièce
Code douanier	8536619090

Downloads Préférés

Fiche produit, informations techniques	1SFC151007C02_
Instructions et manuels	1SFC151011M0201

Dimensions

Produit Largeur Net	0.03 m
Produit Hauteur Net	0.03 m
Produit Longueur Net	0.052 m
Poids net	0.018 kg

Technique

Température de l'air ambiant	Operation -25 ... +70 °C Storage -40 ... +85 °C
Couleur	Yellow
Actuator Type	Pilot light head
Voyant	Illuminated
Type de lampe	230 V AC, integrated LED
Indice de protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Classe de protection (NEMA)	Type1 Type12 Type13 Type3R Type4 Type4X
Degré de pollution	3
Fréquence assignée (f)	Supply Circuit 50 / 60 Hz
Tension	Supply Circuit 230V AC V
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.9 N·m
Wire Stripping Length	8 mm

Technique UL/CSA

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

Environnement

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Informations RoHS	2CMT2015-005451
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

Certificats et Déclarations (Numéro de document)

CB Certificate	CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
Certificat ecULus	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Déclaration de Conformité - CE	2CMT2015-005451
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC-RU C-CN.ME77.B.00690_20

Emballage

Emballage Niveau 1 Unités	bag 10 pièce
Emballage Niveau 1 Largeur	0.235 m
Emballage Niveau 1 Longueur	0.125 m
Emballage Niveau 1 Hauteur	0.035 m
Emballage Niveau 1 Poids	0.184 kg
Emballage Niveau 1 EAN	7320500475508

Classifications

Code de classification d'objet	P
ETIM 6	EC000272 - voyant lumineux, appareil complet
ETIM 7	EC000272 - Indicator light complete
ETIM 8	EC000272 - Indicator light complete
eClass	V11.0 : 27371223
UNSPSC	39121534
Code de catégorie granulaire IDEA (IGCC)	4766 >> Indicator or pilot lights
E-Number (Finland)	2313555
E-Number (Norway)	4373537
E-Number (Sweden)	3705778

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Compact Range → CL Compact Pilot Lights

