


PRODUCT-DETAILS

## A59B

A59B ComfortLine A Wall-mounting cabinet,  
Surface mounted/recessed mounted/partially  
recessed mounted, 540 SU, Isolated (Class II),  
IP00, Field Width: 5, Rows: 9, 1400 mm x 1300  
mm x 215 mm



### Informations générales

Extension du type de produit	A59B
Code de produit	2CPX052092R9999
EAN	4011617520924
Description courte	A59B ComfortLine A Wall-mounting cabinet, Surface mounted/recessed mounted/partially recessed mounted, 540 SU, Isolated (Class II), IP00, Field Width: 5, Rows: 9, 1400 mm x 1300 mm x 215 mm
Description longue	Wall-mounting cabinet, empty cabinet, for the internal use, without door, class of protection II (double insulated), degree of protection IP00, IK code 7, rated current 250 A, Powder-coated, in RAL 9016, enclosure out of sheet steel, without door, door out of sheet steel, cable entry on top via membrane flange mounted, on side via flange opening pre-punched, dimensions in mm (H x W x D): 1400 x 1300 x 215, Grid unit 9 GU, panel width 5, Space units 540, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

### Technique

Courant nominal ( $I_n$ )	250 A
Power Loss	$\Delta t = 20K$ 189.7 W $\Delta t = 25K$ 270.2 W $\Delta t = 30K$ 319.1 W
Number of Flange Openings	5

Number of Conduit Inlets	255
Number of Rows	9
Configuration Type	pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	None
Type de boîtier	Wall-mounting cabinet
Type de montage	Surface mounted/recessed mounted/partially recessed mounted
Door Type	Without Door
Finition de surface	Powder-coated
Qualité du matériau	Steel plate/plastic
Matériau	sheet steel
Style de cache	with Notch
DIN Place Units	540
RAL Number	RAL 9016 - Blanc signalisation
Couleur	Traffic white

## Environnement

Indice de protection	IP00
Classe de protection	Isolated (Class II)
REACH Declaration	2CPC100005X0201
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	60
Produit Largeur Net	1300 mm
Produit Hauteur Net	1400 mm
Produit Longueur Net	215 mm
Poids net	26.891 kg
Profondeur d'encastrement (t <sub>2</sub> )	190 mm
Thickness	Cabinet Plate 0.9 mm Door Plate 0.9 mm

## Commande

Emballage Niveau 1 Unités	pack 1 pièce
Emballage Niveau 1 Poids	27.967 kg

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	No declaration needed
--------------------------------	-----------------------

---

## Installation

---

Instructions et manuels	2CPC133150M5601
-------------------------	-----------------

---



---

## Downloads Préférés

---

Fiche produit, informations techniques	2CPC000001C0101
	2CPC000002C0101
	2CPC000377C0101

---

Building Information Modeling – BIM	9AKK107680A4423;9AKK107680A4422
-------------------------------------	---------------------------------

---



---

## Classifications

---

ETIM 8	EC000058 - Empty cabinet
--------	--------------------------

ETIM 9	EC000058 - Empty cabinet
--------	--------------------------

Catégorie DEEE	Product Not in WEEE Scope
----------------	---------------------------

WEEE B2C / B2B	Business To Consumer
----------------	----------------------

CN8	85381000
-----	----------

eClass	V11.0 : 27142408
--------	------------------

Code de classification d'objet	U
--------------------------------	---

---



---

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CPX052552R9999	CZ11 ComfortLine Interior fitting system, 41.1 mm x 17.25 mm x 33 mm	CZ11	1	piece
2CPX052411R9999	CR59 ComfortLine A Trim frame, IP00, 1450 mm x 1350 mm x 75 mm	CR59	1	piece
2CPX052317R9999	CTB29 ComfortLine Door, IP44, Field Width: 2, 1371 mm x 498 mm x 14 mm	CTB29	1	piece
2CPX052338R9999	CTB39S ComfortLine Door, IP44, Field Width: 3, 1371 mm x 771 mm x 14 mm	CTB39S	1	piece
2CPX052352R9999	CTT29 ComfortLine Door, IP44, Field Width: 2, 1371 mm x 498 mm x 14 mm	CTT29	1	piece
2CPX052373R9999	CTT39S ComfortLine Door, IP44, Field Width: 3, 1371 mm x 771 mm x 14 mm	CTT39S	1	piece
2CPX052387R9999	CTL39S ComfortLine Door, IP30, Field Width: 3, 1371 mm x 771 mm x 14 mm	CTL39S	1	piece
2CPX052401R9999	CTW39S ComfortLine Door, IP30, 1371 mm x 771 mm x 14 mm	CTW39S	1	piece
2CPX052463R9999	CZ5 ComfortLine A Accessory cabinet connection, 69 mm x 12 mm x 36 mm	CZ5	1	piece
2CPX052466R9999	CZC4 Copper busbar connection set, 232 mm x 75 mm x 115 mm	CZC4	1	piece
2CPX052558R9999	CZ11M ComfortLine Interior fitting system, 41.1 mm x 17.25 mm x 33 mm	CZ11M	1	piece
2CPX052461R9999	CZ3 ComfortLine Accessory cabinet connection, 232 mm x 50 mm x 115 mm	CZ3	1	piece
2CPX052559R9999	CZ11P20 ComfortLine Interior fitting system, 41.1 mm x 17.25 mm x 33 mm	CZ11P20	1	piece
2CPX052462R9999	CZ4 ComfortLine Accessory cabinet connection, 20.5 mm x 204 mm x 87 mm	CZ4	1	piece
2CPX052460R9999	CZ2 ComfortLine Accessory cabinet connection, 30 mm x 50 mm x 13 mm	CZ2	1	piece
2CPX052459R9999	CZ1P4 ComfortLine Accessory cabinet assembly, 130 mm x 40 mm x 20 mm	CZ1P4	1	piece
2CPX052458R9999	ZK225T Terminals	ZK225T	1	piece
2CPX052437R9999	CZF3 ComfortLine Flange, 22 mm x 223 mm x 106 mm	CZF3	1	piece
2CPX052438R9999	CZF4 ComfortLine Flange, 22 mm x 223 mm x 106 mm	CZF4	1	piece
2CPX052504R9999	CZB219 ComfortLine Interior fitting system, 1350 mm x 124 mm x 7 mm	CZB219	1	piece
2CPX052553R9999	CZ12 ComfortLine Accessory cabinet assembly, 22 mm x 22 mm x 18 mm	CZ12	1	piece
2CPX052464R9999	CZ6 ComfortLine Flange, 218 mm x 9.9 mm x 98.5 mm	CZ6	1	piece

## Catégories

Produits basse tension → Tableaux, Coffrets et Armoires → Tableaux Divisionnaires → Meter Boards → ComfortLine A

Produits basse tension → Tableaux, Coffrets et Armoires → Tableaux Divisionnaires → Sub Distribution Boards → ComfortLine A

