

PRODUCT-DETAILS

CM-TCS.13P

CM-TCS.13P Temperature monitoring relay Temp.-range 0...+200°C, 24-240VAC/DC



Informations générales

Extension du type de produit	CM-TCS.13P
Code de produit	1SVR740740R0300
EAN	4016779852791
Description courte	CM-TCS.13P Temperature monitoring relay Temp.-range 0...+200°C, 24-240VAC/DC
Description longue	<p>The CM-TCS.13P relay is from the CM temperature monitors range. This relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. The CM-TCS.13P is able to measure temperature with 1 sensor circuit using PT100 sensor. The CM-TCS.13P monitors overtemperature, undertemperature and window monitoring with 2 thresholds. The corresponding threshold values are adjustable. The temperature measuring range is 0..+200°C. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.</p>

Commande

EAN	4016779852791
Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Fiche produit, informations techniques	2CDC112199D0201
Instructions et manuels	1SVC730560M1001

	1SVC730560M0001
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	22.5 mm
Produit Hauteur Net	85.6 mm
Produit Longueur Net	103.7 mm
Poids net	0.14 kg

Technique

Fonction	Overtemperature monitoring Undertemperature monitoring Over- and undertemperature monitoring
Plage de mesure	0 ... +200 °C
Sensor Type	PT100
Rated Control Supply Voltage (U_s)	24 ... 240 V AC/DC
Fréquence assignée (f)	Supply Circuit 50 Hz Supply Circuit 60 Hz Supply Circuit DC
Sortie	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Type de borne	Screwless Terminals
Rated Operational Current AC-12 (I_e)	(230 V) 4 A
Courant assignée d'emploi AC-15 (I_e)	(230 V) 3 A
Rated Operational Current DC-12 (I_e)	(24 V) 4 A
Courant assignée d'emploi DC-13 (I_e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Tension assignée de tenue aux chocs (U_{imp})	Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
Tension assignée d'isolement (U_i)	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Indice de protection	Housing IP50 Terminals IP20
Catégorie de Surtension	III
Degré de pollution	3
Dispositif de protection contre les courts-circuits	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Durabilite mecanique	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Type d'encastrement	1 ... 6
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Normes et standards

CAN/CSA C22.2 No.60947-5-1
 IEC/EN 60255-26
 IEC/EN 60255-27
 IEC/EN 61000-6-2
 IEC/EN 61000-6-3
 IEC/EN 63000
 UL 60947-5-1
 IEC/EN 60947-5-1

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300

Environnement

Température de l'air ambiant	Operation -40 ... +60 °C Storage -40 ... +85 °C
Altitude de fonctionnement maximale autorisée	Without Derating 2000 m
REACH Declaration	1SVD981001-4501
Informations RoHS	1SVD981015-00
Statut RoHS	Following EU Directive 2011/65/EU

Valeur Circulaire

Instructions relatives à la fin de vie	1SAC200290H0001
--	-----------------

Certificats et Déclarations (Numéro de document)

CCC Certificate	CCC_2018010303056014
CQC Certificate	CQC2007010303243843
Certificat ecULus	cULus60947-5-1_20170922-E140448
Declaration of Conformity - CCC	2020980303000196
Déclaration de Conformité - CE	1SVD981015-00
Declaration of Conformity - UKCA	1SVD981015-10
DNV GL Certificate	DNV_GL_TAA000021M
EAC Certificate	EAC_RU_C-DE.ME77.B.03424

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	97 mm
Emballage Niveau 1 Longueur	30 mm
Emballage Niveau 1	109 mm

Hauteur	
Emballage Niveau 1 Poids	0.165 kg
Emballage Niveau 1 EAN	4016779852791

Classifications

Code de classification d'objet	B
ETIM 7	EC001446 - Temperature monitoring relay
ETIM 8	EC001446 - Temperature monitoring relay
ETIM 9	EC001446 - Temperature monitoring relay
eClass	V11.0 : 27371810
UNSPSC	39122331
E-Number (Finland)	2712325
E-Number (Sweden)	3860671

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Contrôle des températures

