

| | | | | |
|---|---------------------------------------|-----|-----------------|---|
| Product designation | | | | Rotary cam switches |
| Product type designation | | | | GN200 |
| General characteristics | | | | |
| Switching diagram | | | | 107 - Multi-step 0-1-2 1 pole |
| N° of elements | | | | 1 |
| Mounting form | | | | O - Rear mounting with black handle |
| Contact characteristics | | | | |
| Rated insulation voltage U_i | IEC/EN | V | 690 | |
| | UL/CSA | V | 600 | |
| Rated impulse withstand voltage U_{imp} | | kV | 8 | |
| Conventional free air thermal current I_{th} | IEC/EN | A | 200 | |
| | UL/CSA | A | 200 | |
| Rated operational voltage | | V | 690 | |
| Rated operational impulse voltage | | kV | 6 | |
| Maximum fuse size for short-circuit protection I_n (gG) | 10kA | A | 200 | |
| | 15kA | A | 200 | |
| Rated short time current I_{cw} | 1s | A | 3300 | |
| Operational current I_e IEC/EN AC1/AC21A | | A | 200 | |
| Rated operational power in AC Three-phase AC-3 | 220/230V | kW | 27.5 | |
| | 380/440V | kW | 47 | |
| Rated operational current in DC DC21A | 48V | A | 200 | |
| | 60V | A | 200 | |
| | 110V | A | 35 | |
| | 220V | A | 2.5 | |
| | 440V | A | 0.9 | |
| Power dissipation | | W | 26 | |
| Mechanical features | | | | |
| Terminals screw | | | | M10 |
| Tightening torque for terminals max | | | | Nm 10 |
| Conductor size | AWG - Rigid cable | Max | AWG | 1X3 |
| | AWG - Flexible cable | Max | AWG | 0 |
| | Conductor size (IEC) - Flexible cable | Max | mm ² | 1X95 |
| | Conductor size (IEC) - Rigid cable | Max | mm ² | 1X95 |
| Mechanical life | | | | cycles 2X10 ⁵ |

UL technical data

Motor power for direct-on-line control

for three-phase motor

| | | |
|------|----|-----|
| 120V | HP | 30 |
| 240V | HP | 50 |
| 480V | HP | 100 |
| 600V | HP | 75 |

for single-phase motor

| | | |
|------|----|----|
| 120V | HP | 15 |
| 240V | HP | 30 |

Ambient conditions

Temperature

Operating temperature

| | | |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +55 |

Storage temperature

| | | |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |

Resistance & Protection

Frontal IP degree


IP40

Terminals IP degree

IP00

Dimensions

Wiring diagrams



Certifications and compliance

Compliance

| |
|---------------------|
| IEC/EN/BS 60947-1 |
| IEC/EN/BS 60947-3 |
| IEC/EN/BS 60947-5-1 |
| UL60947-4-1 |

Certificates

UR

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete