

# Everon® Réseaux Datacom – Gamme Cuivre U/UTP 450/24, Catégorie 6, LSZH™/FRNC, Dca 4P, Vert



**Part Number:**  
**DE010024342**

The Everon® Copper Datacom U/UTP 450/24 cable is designed up to 450MHz and its transmission characteristics exceed Category 6 specifications according to EN50288-6-1 IEC 61156-5. High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable. The cable has a streamlined construction and low weight. Unshielded cable (U/UTP).

## Features and Benefits

U/UTP 450/24 cable designed up to 450 MHz

---

Fulfils all requirements of category 6 EN50288-6-1 and IEC 61156-5

---

Suitable for Classe D to E according to ISO/IEC 11801. EN50173 and 10 Gigabit Ethernet according to IEEE 802.3an

---

Testé et approuvé pour les applications d'alimentation par Ethernet (PoE/PoE+/4PPoE) conformément aux normes IEEE 802.3af, IEEE 802.3at et IEEE 802.3bt jusqu'à 90 W

---

Certified by a vendor-independent and impartial test lab

---

Low smoke and halogen-free (LSZH)

---

Unshielded cable (U/UTP)

---

Length marking on jacket

---

Dca-s2,d2,a1

# Everon® Réseaux Datacom – Gamme Cuivre U/UTP 450/24, Catégorie 6, LSZH™/FRNC, Dca 4P, Vert



## Specifications

General Specifications	
Environment	Indoor
Category	6
Cable type	U/UTP
Bandwidth	450 MHz
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	Dca, s2, d2, a1
Legacy Part Number	VOL6UL4305
Brand	Everon®

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-6-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA-568-C-2; IEC 60304
Design And Test Criteria	1000 Base-T IEEE 802.3 an; PoE / PoE++ IEEE 802.3af, IEEE 802.3at
Flame propagation test	IEC 60332-1
Smoke density	IEC 61034-2
Halogen content test	Zero Halogen to IEC 60754-1

Environmental Conditions	
Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

Cable Design	
Conductor	Copper Wire, AWG 24/1

# Everon® Réseaux Datacom – Gamme Cuivre U/UTP 450/24, Catégorie 6, LSZH™/FRNC, Dca 4P, Vert



## Cable Design

Conductor insulation	Halogen-free foam-skin material
Twisting	2 cores to a pair
Outer jacket material	LSZH/FRNC
Outer jacket colour	Green

## Mechanical Characteristics

Fire load	553 MJ/km
Nominal outer diameter	5.4 mm
Min. bend radius installation	8x Cable-Ø
Maximum tensile strength	100 N

## Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	40 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	520 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Propagation velocity at >10 MHz (NVP*c)	67 %
Coupling attenuation	40 dB
Insulation Resistance	> 5000 MΩ*km

## Ordering Information

Product Number	DE010024342
Weight	324 kg
Packing type	Reelex Box
Units per delivery	1/1

# Everon® Réseaux Datacom – Gamme Cuivre U/ UTP 450/24, Catégorie 6, LSZH™/FRNC, Dca 4P, Vert



Electrical Characteristics								
Frequency [MHz]	4	10	20	63	100	250	300	450
Attenuation according to Standard [db/100m]	3.83	6.0	8.53	15.48	19.92	33.02		46.22
Typical attenuation [db/100m]	3.6	5.7	8.3	14.8	19.0	31.0	34.0	43.0
NEXT according to Standard [db/100m]	66.27	60.3	55.78	48.36	45.3	39.33		35.5
Typical NEXT Values [db/100m]	71.0	65.0	61.0	53.0	50.0	44.0	43.0	40.0
ACR-N according to Standard [db/100m]	55.96	48.0	41.98	32.08	28.0	20.04		14.94
Typical ACR-N Values [db/100m]	67.5	59.3	52.7	38.2	31.0	13.0	9.0	



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2023 Corning Optical Communications. All rights reserved.