
# SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1>0<2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0



Product designation				Selector switch actuator key - 3 position
Product type designation				LPFS37
General characteristics	S			
Colour				Black
Type of positions				Selector switch
Material				Aluminium and zinc alloy
IEC degree of protection				IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			_
		min	°C	-40
		max	°C	+85
Dimensions				

## **Dimensions**



#### Certifications and compliance

## Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

## ETIM classification





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1>0<2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0

ETIM 8.0

EC002611 -Control switch