


Description: 1-gang push button insert (2-pole, 1-way)

Ref.-no.: 532 U

illumination possible with lamp

Can be converted into pull cord push-button by means of pull cord insert.



Contact assignments

## Technical data

Switching voltage: AC 250 V ~  
Switching current: 10 AX  
Connection: screwless terminals  
Switch type: 2-pole, 1-way (NOFermeture bipolaire contact)

## Accessories

Lamp:

Ref.-no.:	90 (230 V, 1.1 mA)
Ref.-no.:	95 (230 V, 0.5 mA)
Ref.-no.:	96-12 (12 V, 40 mA)
Ref.-no.:	96-24 (24 V, 25 mA)
Ref.-no.:	96-36 (36 V, 20 mA)
Ref.-no.:	96-48 (48 V, 25 mA)

LED lamp:

Ref.-no.:	961248 LED RT (red 12 – 48 V, ca. 4 mA)
Ref.-no.:	961248 LED GN (green 12 – 48 V, ca. 4 mA)
Ref.-no.:	90-LED RT (red 230 V, ca. 1.1 mA)
Ref.-no.:	90-LED GN (green 230 V, ca. 1.1 mA)

Pull cord insert:

Ref.-no.:	34
Ref.-no.:	34 KO5