



LEGRAND'S ENVIRONMENTAL COMMITMENTS

• **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

• **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

• **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	Connect a workstation remote from the wall to the energy and communication networks for 20 years, via 12 data/telecoms sockets.
Reference Product	 <p>Cat.No CR012 - CR024 3 compartment Floor Box 85 mm depth single base CR012 - equipped with 3 plates CR024 (without wiring devices).</p>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers
The full Electrak Floor boxes range (2, 3 and 4 compartment empty boxes and accessory plates) without wiring devices, as presented in all relevant catalogues - details available on request from customer service team.



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

Total weight of Reference Product	3512 g (all packaging included)				
Plastics as % of weight		Metals as % of weight		Other as % of weight	
ABS	13.9 %	Steel	76.7 %		
POM	1.0 %				
PU	0.2 %				
Other plastics	0.2 %				
Packaging as % of weight					
PP	< 0.1 %			Paper	7.2 %
				Wood	0.8 %
Total plastics	15.3 %	Total metals	76.7 %	Total others	8.0 %

Estimated recycled material content: 33 % by mass.



■ MANUFACTURE

This Reference Product comes from a site that has received ISO14001 certification.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 220 km by road from our warehouse to the local point of distribution into the market in United Kingdom.

Packaging is compliant with applicable regulation. At their end of life, its recyclability rate is 99 % (in % of packaging weight).



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.



END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

• **Recyclability rate:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 99 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 14 %
- metal materials (excluding packaging) : 77 %
- other materials (excluding packaging) : 0 %
- packaging (all types of materials) : 8 %



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative from products marketed and used in United Kingdom.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.
Installation	The end of life of the packaging.
Use	<ul style="list-style-type: none"> • Product category: « PSR-0003-ed1.1-EN-2015 10 16 cable management solutions - 3.2.3.1. Non-equipped service poles, service posts and multi-outlets extension ». • Use scenario: no energy consumption during the 20 years working life. This modelling duration does not constitute a minimum durability requirement. • Energy model: Electricity Mix; Europe 27 - 2008.
End of life	The default end of life scenario maximizing the impacts.
Software and database used	EIME & database CODDE-2018-11



SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
Global warming	1.44E+01	kgCO ₂ eq.	1.42E+01	98 %	3.85E-02	< 1 %	1.73E-02	< 1 %	0.00E+00	0 %	2.39E-01	2 %
Ozone depletion	1.43E-07	kgCFC-11 eq.	1.40E-07	98 %	7.79E-11	< 1 %	1.11E-10	< 1 %	0.00E+00	0 %	2.77E-09	2 %
Acidification of soils and water	3.75E-02	kgSO ₂ eq.	3.63E-02	97 %	1.73E-04	< 1 %	8.43E-05	< 1 %	0.00E+00	0 %	9.85E-04	3 %
Water eutrophication	5.83E-03	kg(PO ₄) ³⁻ eq.	4.19E-03	72 %	3.97E-05	< 1 %	8.52E-05	1 %	0.00E+00	0 %	1.52E-03	26 %
Photochemical ozone formation	4.72E-03	kgC ₂ H ₄ eq.	4.63E-03	98 %	1.23E-05	< 1 %	5.95E-06	< 1 %	0.00E+00	0 %	7.46E-05	2 %
Depletion of abiotic resources - elements	1.01E-04	kgSb eq.	1.01E-04	100 %	1.54E-09	< 1 %	7.47E-10	< 1 %	0.00E+00	0 %	1.15E-08	< 1 %
Total use of primary energy	7.30E+02	MJ	7.27E+02	99 %	5.44E-01	< 1 %	2.39E-01	< 1 %	0.00E+00	0 %	2.89E+00	< 1 %
Net use of fresh water	2.13E+00	m ³	2.13E+00	100 %	3.44E-06	< 1 %	5.08E-06	< 1 %	0.00E+00	0 %	1.02E-04	< 1 %
Depletion of abiotic resources - fossil fuels	1.64E+02	MJ	1.61E+02	98 %	5.40E-01	< 1 %	2.32E-01	< 1 %	0.00E+00	0 %	2.76E+00	2 %
Water pollution	1.37E+03	m ³	1.33E+03	97 %	6.33E+00	< 1 %	2.69E+00	< 1 %	0.00E+00	0 %	3.22E+01	2 %
Air pollution	1.69E+03	m ³	1.67E+03	99 %	1.58E+00	< 1 %	2.06E+00	< 1 %	0.00E+00	0 %	1.75E+01	1 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.



SELECTION OF ENVIRONMENTAL IMPACTS

The environmental impact of the system, described in this document and different of the Reference Product, can be estimated by weighting the environmental impacts of the Reference Product by the corresponding factors (see under).

Designation	Correction factor to apply to each indicators, for each life cycle steps or to the total life cycle
CR2001 empty box 2 comp single base 75 mm depth - equipped with plates (without wiring devices)	0.76
CR2002 empty box 2 comp single base 85 mm depth - equipped with plates (without wiring devices)	0.77
CR2003 empty box 2 comp single base 110 mm depth - equipped with plates (without wiring devices)	0.90
CR2004 empty box 2 comp separate base 75 mm depth - equipped with plates (without wiring devices)	0.69
CR2005 empty box 2 comp separate base 85 mm depth - equipped with plates (without wiring devices)	0.66
CR2006 empty box 2 comp separate base 110 mm depth - equipped with plates (without wiring devices)	0.79
CR011 empty box 3 comp single base 75 mm depth - equipped with plates (without wiring devices)	1.17
CR012 empty box 3 comp single base 85 mm depth - equipped with plates (without wiring devices)	1.00
CR013 empty box 3 comp single base 110 mm depth - equipped with plates (without wiring devices)	1.12
CR014 empty box 3 comp separate base 75 mm depth - equipped with plates (without wiring devices)	0.85
CR015 empty box 3 comp separate base 85 mm depth - equipped with plates (without wiring devices)	0.82
CR016 empty box 3 comp separate base 110 mm depth - equipped with plates (without wiring devices)	0.94
CR4001 empty box 4 comp single base 75 mm depth - equipped with plates (without wiring devices)	0.99
CR4002 empty box 4 comp single base 85 mm depth - equipped with plates (without wiring devices)	1.01
CR4003 empty box 4 comp single base 110 mm depth - equipped with plates (without wiring devices)	1.14
CR4004 empty box 4 comp separate base 75 mm depth - equipped with plates (without wiring devices)	0.83
CR4004 empty box 4 comp separate base 85 mm depth - equipped with plates (without wiring devices)	0.84
CR4004 empty box 4 comp separate base 110 mm depth - equipped with plates (without wiring devices)	0.96

Registration number: LGRP-01290-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0003-ed1.1-2015 10 16»
Verifier accreditation N°: VH23	Information and reference documents: www.pep-ecopassport.org
Date of issue: 04-2021	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 + A1 : 2013	

