



## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: BATWING  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 1693mm  
A: 60mm  
H: 80mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 5.3kg

## Tech data

Luminaire input power: 55.8W  
Luminaire luminous flux: 6254lm  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: No

## Source

Light source: LED  
Source power: 50W  
Source luminous flux: 6801lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B10

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

**MOUNTING ACCESSORIES**

---



HERO: SOSPL3000 1PZ. TESTA/CODA

**108685.99**

---



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**

---



KIT ALIMENTAZIONE L3000 3P BIA

**108920.01**

---