


PRODUCT-DETAILS

MSA-F-1.1.1-81

MSA-F-1.1.1-81 Mov. detector/actuator 1g



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | MSA-F-1.1.1-81 |
| Code de produit | 2CKA006220A0215 |
| EAN | 4011395179840 |
| Description courte | MSA-F-1.1.1-81 Mov. detector/actuator 1g |

| | |
|--------------------|---|
| Description longue | <p>With select lens for detection with animal access. For automatic switching of ABB-free@home® actuators dependent on movement and brightness. Switch-off delay of the actuator can be programmed via the web interface of the System Access Point. For switching 127 V~/230 V~ consumers. With integrated switch actuator. Switching function is available also without prior programming (pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). The bus can be connected via enclosed terminal block. When installing in the flush-mounted box, a spatial division between the bus cable and 127 V/230 V installation cable is to be adhered to! If this minimum distance is not possible, use electronic boxes or insulating tubes.</p> |
|--------------------|---|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CKA001173B8559 |
| Courant nominal (I_n) | 10 A |

| | |
|-------------------------|--|
| Maximum Switching Power | 2300 W |
| Nombre de sorties | 1 |
| Number of Channels | 1 |
| Compatible Bus Systems | free@home |
| Product Range | free@home |
| Design Range | 63x63 future linear Busch-axcent Busch-axcent pur Busch-Dynasty carat |
| Minimum Switching Time | Switch-On 30 second [unit of time] |
| Type de charge | ohmic |
| Type de montage | Flush Mounted |
| Finition de surface | Surface protection: Untreated Surface finishing: Glossy |
| Matériau | Thermoplastic |
| Type d'encastrement | vertical |
| Model Number | Movement sensor |
| RAL Number | RAL 7021 - Gris noir |
| Couleur | anthracite |
| Nombre de batteries | 0 |
| Application Function | Electrical Load and Light Control |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E4991 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|-------|
| Produit Largeur Net | 71 mm |
| Produit Hauteur Net | 71 mm |
| Produit Longueur Net | 56 mm |
| Poids net | 90 g |
| Profondeur d'encastrement (t ₂) | 32 mm |

Commande

| | |
|------------------------|-------------|
| ID du produit remplacé | 6220-0-0215 |
|------------------------|-------------|

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E1379 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001582 - Movement sensor for bus system |
| ETIM 9 | EC001582 - Movement sensor for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8536 50 80 |
| eClass | V11.0 : 27143144 |

Catégories

Produits basse tension → Home and Building Automation → free@home → User Operation → Solo → Motion Detectors

