

PRODUCT-DETAILS

E 91/30s CC

E 91/30s CC Fuse holder



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | E 91/30s CC |
| Code de produit | 2CSM299882R1801 |
| EAN | 8012542998822 |
| Description courte | E 91/30s CC Fuse holder |
| Description longue | E 91/30S CC is a fuseholder for overcurrent and short circuit protection specific for class CC fuses |

Technique

| | |
|--|--|
| Normes et standards | UL 4248-1 UL 4248-4 |
| Tension nominale (U_n) | 600 V |
| Tension assignée d'isolement (U_i) | 1+2* U_n kV |
| Auxiliary Voltage AC/DC | LED Indicator 24-1000 V AC/DC |
| Courant nominal (I_n) | 30 A |
| Fréquence assignée (f) | 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 3 W |
| Number of Protected Poles | 1 |
| Nombre de pôles | 1 |
| Couple de serrage | 2-2.5 N·m |

| | |
|---|--|
| Type de fusible | class CC |
| Lock Type | Padlockable |
| Type de montage | DIN-Rail |
| Type d'étanchéité | Sealing Wire |
| Material of Conductor | Copper |
| Options Provided | With LED |
| Recommended Screw Driver | Pozidriv 2 |
| Remarques | For use with CU only 60°C, 75°C or 90°C wire |
| Shock and Vibration Withstand acc. to IEC 61373 | Category 1, Class B |
| Connecting Capacity | Stranded 1x1.5...16 mm ² Stranded 2x2...5 mm ² Rigid 1x1.5...25 mm ² Rigid 2x5 mm ² |
| Taille de fusible | 10x38 mm max. 90% at +20 °C 50% at max. +40 °C |

Environnement

| | |
|--|---|
| Température de l'air ambiant | Operation -5...+40 °C Storage -25...+70 °C |
| Indice de protection | IP20 |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 2 to 13 Hz x= 1 mm peak 13 to 100 Hz y= 0.7 g peak |
| Résistance aux chocs selon CEI 60068-2-27 | 15g 18 shocks 11 ms |
| Statut RoHS | Following EU Directive 2011/65/EU |
| Informations RoHS | 9AKK107045A7301 |
| REACH Declaration | 9AKK108467A9482 |
| Informations environnementales | See RoHS Information |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Technique UL/CSA

| | |
|----------------------------|--|
| Connecting Capacity UL/CSA | Stranded 1x16...3 AWG Stranded 2x14...10 AWG Rigid 1x16...10 AWG Rigid 2x10 AWG |
| Tightening Torque UL/CSA | 18-22 in-lb |

Dimensions

| | |
|---|----------|
| Width in Number of Modular Spacings | 1 |
| Produit Largeur Net | 0.018 m |
| Produit Hauteur Net | 0.085 m |
| Produit Longueur Net | 0.064 m |
| Poids net | 0.067 kg |
| Profondeur d'encastrement (t ₂) | 64 mm |

Commande

| | |
|---------------------------|-------------|
| Emballage Niveau 1 Unités | box 6 pièce |
| Emballage Niveau 1 Poids | 0.396 kg |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Agence de certification | UL |
| Déclaration de Conformité - CE | 9AKK107045A7301 |
| Certificat UL | 9AKK107992A1037 |

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CSC444002B0204 |
|--|-----------------|

Classifications

| | |
|--|--|
| ETIM 8 | EC002705 - Holder for cylindrical fuse |
| ETIM 9 | EC002705 - Holder for cylindrical fuse |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85361050 |
| UNSPSC | 39121624 |
| eClass | V11.0 : 27142121 |
| Code de catégorie granulaire IDEA (IGCC) | 4974 >> Holder for cylindrical fuse |
| Code de classification d'objet | F |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors

