



LCIE

# LICENCE



**LCIE N° : 671472/A2**

Titulaire :  
*License Holder:*

**SCHNEIDER ELECTRIC INDUSTRIES SAS**  
35, rue Joseph Monier  
92500 RUEIL MALMAISON -France

Site de fabrication :  
*Factory:*

**SCHNEIDER ELECTRIC ESPANA SA**  
Ctra de Pamplona a Logroño, s/n ;  
31100 PUENTE LA REINA, NAVARRA - Espagne

(N°1146AP)

Produit :  
*Product:*

**Socle fixe de prise de courant**  
*Fixed socket-outlet*

Marque commerciale (s'il y a lieu) :  
*Trade mark (if any):*



Modèle, type, référence :  
*Model, type, reference:*

Gamme / *Series* : ODACE and/et SEQUENCE 5  
Références : voir annexe / *References: see annex*

Caractéristiques principales :  
*Main characteristics:*

Voir Annexe / *See Annex*

Informations complémentaires :  
*Additional information:*

Voir Annexe / *See Annex*

Le produit est conforme à :  
*The product is in conformity with:*

NF C 61-314:2008 +A1:2010

Documents pris en compte :  
*Relevant documents:*

Rapport(s) d'essai(s) / *Test report(s)* n° LME06/3246-1-1i / 10\_R3,  
n° 117508-635261, 135239-671470A, 145019-694009

Annule et remplace (s'il y a lieu) :  
*Cancels and replaces (if necessary):*

La licence / *License* 671472/M1 du/of 31/01/2017 : correction  
éditoriale/editorial correction

En vertu de la présente décision notifiée par le LCIE organisme mandaté, AFNOR Certification accorde le droit d'usage de la Marque NF à la société qui en est titulaire pour les produits visés ci-dessus, dans les conditions définies par les règles générales de la Marque NF et par les règles de certification NF, pour autant que les contrôles réguliers de la fabrication et les vérifications par tierce partie soient satisfaisants.


*On the strength of the present decision notified by LCIE mandated certification body, AFNOR Certification grants the right to use the NF Mark to the licence holder for the above mentioned products, within the frame of the general rules of the NF Mark and of the NF certification rules, as far as the regular checking and third party verifications of the production are satisfactory.*

Fontenay-aux-Roses, 01/02/2019

Date de fin de validité / *Expiry date* :

La validité de la présente licence cesse dès l'annulation de l'une des normes sur lesquelles elle est fondée.

*The present license is valid until the cancellation of one of the standards on which it is based.*



**Jean-François BRUEL**  
Responsable Certification/Certification Officer



Accréditation  
N° 5-0014

Portée disponible sur  
www.cofrac.fr

LCIE

Laboratoire Central des Industries Electriques  
Une société de Bureau Veritas

33 Avenue du Général Leclerc  
92260 Fontenay-aux-Roses  
FRANCE

WWW.LCIE.FR

## Annexe de la licence / Annex of license 671472/A2

### RÉFÉRENCES, CARACTÉRISTIQUES PRINCIPALES REFERENCES, MAIN CHARACTERISTICS

Références de type <i>Type references</i>	Références <i>References</i>	Nombre de pôles <i>Number of poles</i>	Type de bornes <i>Type terminals</i>	Information additionnelle <i>Additional information</i>
417105	S5xy033	2P (IIIA)	vis / screw	ODACE
417088	S5xy039	2P+T (I)	vis / screw	ODACE
	S5xy059	2P+T (I)	sans vis screwless	ODACE
417087	S800059xx			SEQUENCE 5, 1 poste / 1 gang
	S800259xx			SEQUENCE 5, 2 postes / 2 gangs
	S800359xx			SEQUENCE 5, 3 postes / 3 gangs
417104	S5xyA59	2P+T (I)	sans vis screwless	ODACE, avec neutre repéré <i>with neutral position</i>
417089	S5xy099	2P+T (I)	vis / screw	ODACE, à détrompage / <i>tamperproof</i>

xx = couleur / *color*

#### Signification du code / *Meaning of code S5xy---*

Composition	Capot blanc <i>White cover</i>	Capot aluminium <i>Aluminum cover</i>	Capot anthracite <i>Anthracite cover</i>	Lieux de vente <i>Sales location</i>
Base + Support + Capot <i>Main part + Fixing frame + Cover</i>	S520---	S530---	S540---	professionnels <i>professional</i>
	S523---	S533---	S543---	commerce <i>trade</i>
Base + Support + Capot + Enjoliveur <i>Main part + Fixing frame + Cover + Cover plate</i>	S521---	S531---	S541---	professionnels <i>professional</i>
Base + Support + Capot + Griffes <i>Main part + Fixing frame + Cover + Claws</i>	S522---	S532---	S542---	professionnels <i>professional</i>
	S525---	S535---	S545---	commerce <i>trade</i>

Feuille de norme / <i>Standard Sheet</i>	I et / <i>and</i> IIIA
Courant nominal / <i>Rated current (A)</i>	16 A
Tension nominale / <i>Rated voltage (V)</i>	250 V~
Degré de protection / <i>degree of protection</i>	IP20
Présence de contact de terre <i>Provision for earthing</i>	sans contact de terre / <i>without earthing contact</i> (IIIA) avec contact de terre / <i>with earthing contact</i> (I)
Procédé de raccordement du câble <i>Method of connecting the cable</i>	démontable <i>rewirable</i>
Type des bornes <i>Type of terminals</i>	bornes à vis / <i>screw-type</i> sans vis (rigide et souple) / <i>screwless (rigid and flexible)</i>
Degré de protection contre les chocs électriques <i>Degree of protection against electric shock</i>	protection augmentée <i>increased protection</i>
Présence des obturateurs <i>Existence of shutters</i>	avec obturateurs <i>with shutters</i>
Mode de pose - utilisation <i>Method of application - mounting</i>	encastré <i>flush-type</i>
Procédé d'installation <i>Method of installation</i>	S5----- : conception A / <i>design A</i> S800----- : conception B / <i>design B</i>

## Annexe de la licence / Annex of license 671472/A2

### Accessoires / Accessories

Type	R2f. type Type ref.	Remarques Remarks
Enjoliveur 1 poste "Basic" Cover plate 1 gang "Basic"	S520702x	Le dernier "x" correspond à la couleur <i>The last "x" corresponds to the colour</i> V57 = vertical - entre-axe 57mm V57 = vertical - between - axis 57mm
Enjoliveur 2 postes "Basic" Cover plate 2 gang "Basic"	S520704x	
Enjoliveur 3 postes "Basic" Cover plate 3 gang "Basic"	S520706x	
Enjoliveur 4 postes "Basic" Cover plate 4 gang "Basic"	S520708x	
Enjoliveur 2 postes "Basic" V57 Cover plate 2 gang "Basic" V57	S520714x	
Enjoliveur 3 postes "Basic" V57 Cover plate 3 gang "Basic" V57	S520716x	
Enjoliveur 1 poste "Basic" avec appui Cover plate 1 gang "Basic" with support	S520712x	Le dernier "x" correspond à la couleur <i>The last "x" corresponds to the colour</i>
Enjoliveur 1 poste "Basic" avec support Cover plate 1 gang "Basic" with holder	S5207x2x	
Enjoliveur 1 poste "Basic" avec pince Cover plate 1 gang "Basic" with Clip	S5207x2x	
Enjoliveur 1 poste "Basic" avec capot Cover plate 1 gang "Basic" with Lid	S520752x	
Enjoliveur 1 poste "In two" Cover plate 1 gang "In two "	S5x0802x	Le premier "x" est marqué 2 pour les références faites en PC seulement <i>The first "x" is marked as "2" for references made in PC only.</i> Le dernier "x" correspond à la couleur <i>The last "x" corresponds to the colour</i> V57 = vertical - entre-axe 57mm V57 = vertical - between - axis 57mm
Enjoliveur 2 postes "In two" Cover plate 2 gang "In two "	S5x0804x	
Enjoliveur 3 postes "In two" Cover plate 3 gang "In two "	S5x0806x	
Enjoliveur 4 postes "In two" Cover plate 4 gang "In two "	S5x0808x	
Enjoliveur 2 postes "In two" V57 Cover plate 2 gang "In two V57"	S5x0814x	
Enjoliveur 3 postes "In two" V57 Cover plate 3 gang "In two " V57	S5x0816x	
Boîtes montage en saillie 1 poste "Basic" Surface box 1gang "Basic"	S520762	Certifiées / Certified NF EN 60670-1 Licence NF 603415B
Boîtes montage en saillie 2 postes "Basic" Surface box 2 gang "Basic"	S520764	