

PRODUCT-DETAILS

6855 AGM-208-500

Outdoor Movement Detector MasterLINE silver metallic



Informations générales

Extension du type de produit	6855 AGM-208-500
Code de produit	2CKA006800A2612
EAN	4011395163238
Description courte	Outdoor Movement Detector MasterLINE silver metallic

Description longue

Electronic movement detector for detecting thermal motion. Remote operation via IR remote control 6841-101. Remote configurable via IR service remote control 6842-101. With display for detection and operation mode. With ground surveillance. With high-quality lens for optimum detection. Detection sensitivity adjustable via IR service remote control. Adjustment of detection range via rotary control element. Surveillance density: 25 sectors with 100 switching segments. With integrated dismantling protection. All functions controlled by microprocessor. Continuous light (4 hours), light deactivation (4 hours) and presence simulation can be activated via IR remote control. Reading in the current brightness value as switching threshold via remote control. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With brightness-independent test mode for evaluating the detection zone. Individual adjustment of detection range via enclosed protective foil which can be cut to size. Additional possibility for switch-on via normally open push-button switch. Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable.

Installation

Instructions et manuels	DEBJE-0073-1-8049
-------------------------	-------------------

Technique

Fiche produit, informations techniques	No document needed
Tension nominale (U _r)	230 V
Auxiliary Voltage AC/DC	230 V AC/DC
Type de tension	AC
Courant nominal (I _n)	10 A
Current Range	Maximum 80 A
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50 ... 60 Hz
Maximum Switching Power	2300 W
Power Loss	1 W
Nombre de sorties	1
Number of Switching Zones	1
Conception	MasterLINE
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de raccordement	Cable Clamp
Type de charge	ohmic, capacitive and inductive loads
Type de montage	Surface Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Thermoplastic
Type d'encastrement	Wall mounted installation
Flux lumineux	3 ... 150 lx
Model Number	Movement sensor
Couleur	silver metallic
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C
Indice de protection	IP55
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6440
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	125 mm
Produit Hauteur Net	33 mm
Produit Longueur Net	100 mm
Poids net	325 g

Commande

ID du produit remplacé	6800-0-2612
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité
- CE

2CKA100000E2066

Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Outdoor Movement Detector → Professional Series

