


PRODUCT-DETAILS

# E 93/125s

## E 93/125s Fuse disconnecter



### Informations générales

Extension du type de produit	E 93/125s
Code de produit	2CSM204922R1801
EAN	8012542586425
Description courte	E 93/125s Fuse disconnecter
Description longue	E 90 50/125 fuse holders are appropriate to protect against overloads and short circuits. They are designed for use with cylindrical fuses from 50 to 125 A.

### Technique

Adapté pour	E 90
Adapté pour la classe de produit	Fuse holders
Tension nominale (U <sub>r</sub> )	acc. To IEC 690 V acc. To UL 690 V
Tension	AC-20B 690 V
Tension assignée d'isolement (U <sub>i</sub> )	1 kV
Fréquence assignée (f)	50/60 Hz
Power Loss	at Rated Operating Conditions per Pole 9.5 W
Number of Protected	3

## Poles

Nombre de pôles	3
Couple de serrage	3.5...4 N·m
Utilization Category	Connecting and disconnecting under no-load conditions - occasional actuation (AC-20B)
Lock Type	Padlockable
Type de montage	DIN-Rail
Type d'étanchéité	Sealing Wire
Material of Conductor	Copper
Options Provided	With LED
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Rigid 4...35 mm <sup>2</sup> Rigid Stranded 4...50 mm <sup>2</sup>
Taille de fusible	22x58 mm max. 90% with temp. +20 °C   50% with max. temp. +40 °C
Rated Operational Current AC (I <sub>e</sub> )	125 A

## Environnement

Température de l'air ambiant	Storage -5...+40 °C Storage Operation   -25...+70 °C
Indice de protection	IP20
Resistance to Vibrations acc. to IEC 60068-2-6	2 to 13 Hz x= 1 mm peak 13 to 100 Hz y= 0.7 g peak
Résistance aux chocs selon CEI 60068-2-27	15g 18 shocks 11 ms
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CSC444009D2701
REACH Declaration	9AKK108467A9482
Informations environnementales	See RoHS Information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	6
Produit Largeur Net	0.105 m
Produit Hauteur Net	0.112 m
Produit Longueur Net	0.07326 m
Poids net	0.405 kg
Profondeur d'encastrement (t <sub>2</sub> )	73.26 mm

## Commande

Emballage Niveau 1	box 1 pièce
Unités	
Emballage Niveau 1 Poids	0.54 kg

---

## Certificats et Déclarations (Numéro de document)

Certificat BV	9AKK108467A0329
CCC Certificate	9AKK108467A0344
Agence de certification	BV, Korean register, CCC, EAC, UL
Déclaration de Conformité - CE	2CSC444009D2701
EAC Certificate	9AKK107992A1034
Certificat KRS	9AKK108467A0338
Certificat LR	9AKK108467A0332
Certificat RINA	9AKK107992A0866
Certificat UL	9AKK107992A1042

---

## Installation

Instructions et manuels	No document needed
-------------------------	--------------------

---

## Downloads Préférés

Fiche produit, informations techniques	2CSC444002B0204
---	-----------------

---

## Classifications

ETIM 8	EC002705 - Holder for cylindrical fuse
ETIM 9	EC002705 - Holder for cylindrical fuse
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85361090
UNSPSC	39121624
eClass	V11.0 : 27142121
Code de catégorie granulaire IDEA (IGCC)	4974 >> Holder for cylindrical fuse
Code de classification d'objet	F

---

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSM257183R1801	E 9F22 GG4 Fuse link	E 9F22 GG4	1	piece
2CSM259283R1801	E 9F22 GG6 Fuse link	E 9F22 GG6	1	piece
2CSM258103R1801	E 9F22 GG8 Fuse link	E 9F22 GG8	1	piece
2CSM256923R1801	E 9F22 GG10 Fuse link	E 9F22 GG10	1	piece
2CSM259403R1801	E 9F22 GG12 Fuse link	E 9F22 GG12	1	piece
2CSM258223R1801	E 9F22 GG16 Fuse link	E 9F22 GG16	1	piece
2CSM257043R1801	E 9F22 GG20 Fuse link	E 9F22 GG20	1	piece
2CSM259533R1801	E 9F22 GG25 Fuse link	E 9F22 GG25	1	piece
2CSM258353R1801	E 9F22 GG32 Fuse link	E 9F22 GG32	1	piece
2CSM257173R1801	E 9F22 GG40 Fuse link	E 9F22 GG40	1	piece
2CSM259393R1801	E 9F22 GG50 Fuse link	E 9F22 GG50	1	piece
2CSM258213R1801	E 9F22 GG63 Fuse link	E 9F22 GG63	1	piece
2CSM257033R1801	E 9F22 GG80 Fuse link	E 9F22 GG80	1	piece
2CSM259523R1801	E 9F22 GG100 Fuse link	E 9F22 GG100	1	piece
2CSM258343R1801	E 9F22 GG125 Fuse link	E 9F22 GG125	1	piece

## Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors

