


### 24x4 FiberRunner® Routing System

#### Cable Fills for 24x4 FiberRunner® Routing System

The maximum amounts may vary according to the cable fill installation methods, straightness of cables, etc.



24x4 FiberRunner® Cable Routing System								
Fill/Pile Up	Internal Area (in²)	Diameter 1.6mm 0.063"	Diameter 2.0mm 0.079"	Diameter 3.0mm 0.118"	Fiber Optic Ribbon Interconnect Cable Diameter 5.20mm 0.205"	Category 6A (SD) Diameter 6.1mm 0.240"	Category 6A Diameter 7.6mm 0.300"	Category 6 Diameter 6.1mm 0.240"
<b>40% Fill</b>								
2" Pile Up	48.1	6174	3951	1756	583	425	272	425
3" Pile Up	72.4	9293	5947	2643	877	640	410	640
4" Pile Up	98.6	12656	8099	3600	1195	872	558	872
<b>50% Fill</b>								
2" Pile Up	48.1	7718	4939	2195	729	532	340	532
3" Pile Up	72.4	11616	7434	3304	1097	800	512	800
4" Pile Up	98.6	15820	10124	4500	1494	1090	697	1090
<b>60% Fill</b>								
2" Pile Up	48.1	9261	5927	2634	874	638	408	638
3" Pile Up	72.4	13940	8921	3965	1316	960	615	960
4" Pile Up	98.6	18984	12149	5400	1792	1308	837	1308

**Channel cutting instructions:** For optimum results, use a miter box and saw. For larger quantities use a plastic cutting saw blade for clean, burr-free cuts. Recommend: Carbide 80T and 100T; .090" thickness, .125" kerf.

The above cable diameters represent the nominal Panduit cable diameter per performance level. For specific cable fill information based on specific part numbers, please contact Panduit customer service.

### 24x4 FiberRunner® Routing System – Channel and Cover

- Robust, large capacity 24x4 system ideal for use with large cable counts
- QuikLock™ Couplers and Brackets reduce system installation time dramatically
- Channel, covers, fittings and other non-metallic system components made from V-0 flame class rated material
- Compatible with all sizes of Panduit® FiberRunner® and Routing Systems, cable management, and racks



FR24X4



FRCV24

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>FR24X4YL10</b>	Used to carry cables horizontally throughout the system. Use QuikLock™ Coupler FRBC24X4YL to attach channel and/or fittings.	10	20

#### 24x4 Snap-On Cover

<b>FRCV24YL10</b>	Optional snap-on cover for channel FR24X4YL10. Supplied in four 30" long pieces.	10	—
-------------------	--	----	---

For other colors replace YL (Yellow) with OR (Orange) or BL (Black). Order number of feet required, in multiples of standard 10' length increments.

### 24x4 FiberRunner® QuikLock™ Coupler

- Pre-assembled to provide fast mechanical assembly of components
- No tools required for installation; bolts loosen for component disassembly
- For other standard colors replace suffix YL (Yellow) with OR (Orange) or BL (Black)

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>FRBC24X4YL</b>	Pre-assembled coupler quickly joins two sections of channel and/or fittings. Mechanically attaches without tightening bolts. Bolts release using 3/8" nut driver to allow coupler to be removed if necessary.	1	5

For other colors replace suffix YL (Yellow) with OR (Orange) or BL (Black).