


PRODUCT-DETAILS

# US/U4.2

## US/U4.2 Universal Interface, 4-fold, FM



### Informations générales

Extension du type de produit	US/U4.2
Code de produit	GHQ6310070R0111
EAN	4016779564816
Description courte	US/U4.2 Universal Interface, 4-fold, FM
Description longue	The Universal Interface has 4 channels which can be parameterised as inputs or outputs, e.g. for connection of conventional push-buttons, auxiliary contacts, LEDs and electronic relays ER/U 1.1. Requires ETS2 V1.2a.

### Installation

Instructions et manuels	GHQ6307072P0004
Installing and Commissioning Manual	2CDC504019D0201

### Technique

Fiche produit, informations techniques	2CDC504021D0201 2CDC504023D0202
Sub-Function	LED controlling
Type de tension	pulsed
Power Loss	0.25 W
Nombre de sorties	4

Compatible Bus Systems	KNX (TP)
Product Range	KNX
Type de montage	Flush Mounted
Manual Operation	Non
Couleur	white
Nombre de batteries	0

## Environnement

Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	2CDK510013D2701
REACH Declaration	9AKK107492A1906
SCIP	87401064-b528-4b2c-b2eb-7d74cd853bd4 Germany (DE)
SCIP simplifié	87401064-b528-4b2c-b2eb-7d74cd853bd4 Germany (DE)
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Produit Largeur Net	12 mm
Produit Hauteur Net	39 mm
Produit Longueur Net	40 mm
Poids net	0.044 kg

## Certificats et Déclarations (Numéro de document)

CB Certificate	9AKK107991A3201
Déclaration de Conformité - CE	2CDK510013D2701
KNX Certificate	9AKK105710A0119

## Classifications

ETIM 8	EC001584 - I/O device for bus system
ETIM 9	EC001584 - I/O device for bus system
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8517 62 00
eClass	V11.0 : 27143145
Code de classification d'objet	A

## Catégories

Produits basse tension → Home and Building Automation → KNX → Standard Inputs → Universal Interfaces

