# DATA SHEET

Valid from: 01.10.2020 SILVYN® FPAG DUO



SILVYN® FPAG DUO is a conduit gland with an fast connector and integrated cable gland. Can remove by using a screw driver.



Body Polyamide Sealing NBR



#### **Technical Features:**

Connecting thread M16x1,5 up to M25x1,5

Nominal width NW 16 up to NW 25

Protection class IP66 acc. to EN 60529
In combination with SILVY® FPAS

Temperature range -20°C up to +100°C

#### **Additional features:**

Free of halogen und lead UV-Resistant

Color: black

Approvals:

**Reference standards:**DIN EN 61386-1
DIN EN 61386-22

Suitable conduits: SILVYN® FPAS

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: MAAU1/PDP Document: DB61805112EN Version: 00 Page 1 of 2

6180 5112	DATA SHEET	Ø I ADD
Valid from: 01.10.2020	SILVYN <sup>®</sup> FPAG DUO	<b>WLAPP</b>

## **Product drawing:**

### Dimension table:

Part No.	NW	Thread	Thread- length mm	Length mm	Inner Diameter mm	Outer Diameter mm	sw	Weight g		
Part Description										
Part Description										