1SET315231R0000 ACTIVE

ENTRELEC | M12 Connector

TE Internal #: 1SET315231R0000

M12 Pigtail Cable Assembly, 2 Position, 1 m, Industrial Fieldbus,

PROFIBUS, Code B, M12 Socket, Shielded, Single Ended,

PA66+25GF

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies











M8/M12 Application Type: Industrial Fieldbus

Industrial Protocols: PROFIBUS

Number of Positions: 2

Keying Code: **B**

Connector Type (End A): M12 Socket

Features

Product Type Features

LED	Without
Product Type	Cable Assembly
Cable Type	PUR
Assembly Type	Overmolded
Connector Type (End A)	M12 Socket
Cable Assembly Type	M12 Pigtail
Configuration Features	
Number of Positions	2
Keying Code	В
Electrical Characteristics	
Operating Voltage	250 VDC
Body Features	

Right Angle

IP67

Cable Exit Angle

Environmental Protection



Conductor Material	Copper Alloy
Connector Color	Black
Cable Jacket Color	Violet
Contact Features	
Contact Current Rating	4 A
Mechanical Attachment	
Connector Orientation (End A)	Right Angle
Housing Features	
Housing Material	PA66+25GF
Dimensions	
Overall Outside Cable Diameter	8 mm
Wire Size	22 AWG
Operation/Application	
M8/M12 Application Type	Industrial Fieldbus
Shielded	Yes
Industry Standards	
Industrial Protocols	PROFIBUS
Packaging Features	
Packaging Method	Bag
Packaging Quantity	5
Other	
Cable Assembly Length	1 m
Cable Assembly Configuration	Single Ended

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)



Candidate List Declared Against: JUNE 2022 (224)

SVHC > Threshold:

Pb (1.9% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach


Compatible Parts








Also in the Series M12 Connector





Documents



Product Drawings

M12B2-FR-PUR TORSION-1.0M

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SET315231R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SET315231R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SET315231R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Infographic - entrelec ews-linecard

English

Catalog - ENTRELEC-M8-M12-RJ45

English

Product Specifications

Application Specification

English