


**Product Description:**

Les spots E5™ et E8™ établissent un nouveau niveau de performance en matière d'encastré LED. Equipés de la lentille faible éblouissement EnFiniti™, ils délivrent jusqu' 390lm en version 4,5W et 640lm en version 8W. Ils sont conçus pour offrir des performances et des économies d'énergie optimales l'utilisateur final tout en garantissant une installation rapide et rentable. Ils sont testés coupe-feu dans les plafonds ignifugés et sont compatibles RT2012 pour les versions fixes.


**Product Image:**



**Line Drawing**



**Polar Curve**



**Product Specs:**

|                                      |            |                                      |              |
|--------------------------------------|------------|--------------------------------------|--------------|
| <b>Technology</b>                    | LED        | <b>Input Voltage</b>                 | 220-240V AC  |
| <b>Positional Adjustment</b>         | Orientable | <b>Positional Adjustment (°)</b>     | 20           |
| <b>Number of LEDs</b>                | 6          | <b>Luminaire Distribution</b>        | Accentuation |
| <b>Lifetime L70 (hrs)</b>            | 25000      | <b>Input Frequency</b>               | /50HZ        |
| <b>Dimmable</b>                      | Oui        | <b>IP Rating</b>                     | IP20         |
| <b>Fire Protection</b>               | Oui        | <b>Acoustic Rated</b>                | Oui          |
| <b>Operating Env. Temp. (Min) °C</b> | -20°C      | <b>Operating Env. Temp. (Max) °C</b> | 25°C         |
| <b>Optic Material</b>                | PMMA       | <b>Power Factor</b>                  | 0.7          |
| <b>Overall Diameter (mm)</b>         | 88         | <b>Height (mm)</b>                   | 90           |
| <b>Recess Depth (mm)</b>             | 90         | <b>Length (mm)</b>                   | 90           |
| <b>Cutout Diameter (mm)</b>          | 75         | <b>Weight (Kg)</b>                   | 0.260        |

**SKU Table and Ordering:**

| SKU Code     | Wattage | Beam Angle | Lumens | Lumens/Watt | CRI | Colour | Finish Colour |
|--------------|---------|------------|--------|-------------|-----|--------|---------------|
| EN-DE52MW/30 | 4.5     | 60         | 420    | 94          | 80  | 3000   | Blanc mat     |
| EN-DE52MW/40 | 4.5     | 60         | 440    | 98          | 80  | 4000   | Blanc mat     |
| EN-DE52PC/30 | 4.5     | 60         | 420    | 94          | 80  | 3000   | Chromé        |
| EN-DE52PC/40 | 4.5     | 60         | 440    | 98          | 80  | 4000   | Chromé        |
| EN-DE52SN/30 | 4.5     | 60         | 420    | 94          | 80  | 3000   | Alu brossé    |
| EN-DE52SN/40 | 4.5     | 60         | 440    | 98          | 80  | 4000   | Alu brossé    |
| EN-DE52W/30  | 4.5     | 60         | 420    | 94          | 80  | 3000   | Blanc         |
| EN-DE52W/40  | 4.5     | 60         | 440    | 98          | 80  | 4000   | Blanc         |

## Compliance & Approvals:

---



## Warranty:

---

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

**UK Head Office**  
Apex Park  
6 Little Burrow  
Welwyn Garden City AL7 4SW  
United Kingdom  
Tel : +44 (0) 1727 83 66 11