



Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD
 Emission: DIRECT
 Optics: SPOT
 Beam: 60°
 Colour: WHITE
 Dimming: ON/OFF
 Emergency: WITH ACCESSORY
 L: Ø172mm
 H: 90mm
 D: 150-165mm
 Warranty: 5 years
 Weight: 1kg

Tech data

Luminaire input power: 24W
 Luminaire luminous flux: 2411lm
 Luminous flux in emergency: 1h: 19% / 3h: 8%
 IP: 40
 Insulation class: II
 Supply voltage: 220-240V 50/60Hz
 SELV: Si

Source

Light source: LED
 Source power: 22W
 Colour temperature: 4000K
 CRI: >90
 LED lifespan: 50000h L80 B50

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99