


Product Description:

Conçue pour durer dans un environnement difficile, l'applique murale UtiliteXL™ avec base en fonte d'aluminium et diffuseur en polycarbonate est disponible en version standard avec capteur hyperfréquence, photocellule crépusculaire ou pack emergency.


Product Image:



Line Drawing



Polar Curve



Product Specs:

Technology	LED	Input Voltage	220-240V AC
Lamp Base	Aucun	Positional Adjustment	Fixe
Number of LEDs	60	Luminaire Distribution	Ambiance
Lifetime L70 (hrs)	25.000	Input Frequency	50/60HZ
Dimmable	Non	IP Rating	IP65
IK Rating	IK10	Fire Protection	No
Operating Env. Temp. (Min) °C	-20°C	Operating Env. Temp. (Max) °C	45°C
Optic Material	Polycarbonate	Power Factor	0.9
Height (mm)	309	Length (mm)	309
Width (mm)	264	Weight (Kg)	1.965

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	CRI	Colour	Finish Colour
EN-WP103/40	30	120	2550	85	80	4000	Noir
EN-WP103EM/40	30	120	2550	85	80	4000	Noir
EN-WP103PH/40	30	120	2550	85	80	4000	Noir

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1727 83 66 11