



Mounting adapter with contact element for LPS and LPF LPXE10M

Product designation

Product type designation

Electrical characteristics

IEC Conventional free air thermal current I _{th}	A	10
UL/CSA and IEC/EN 60947-5-1 designation	A300 Q300	
Operating current AC15	12V	A 6
	24V	A 6
	48V	A 6
	120V	A 6
	240V	A 3

Operating current DC13

12V	A	0.55
24V	A	0.55
48V	A	0.55
125V	A	0.55
250V	A	0.27

Contact resistance mΩ ≤20

Mechanical features

Mechanical life	cycles	1000000
Tightening torque for terminals max	Nm	1

Terminals screw Clamp screw with washer

Mounting adapter Included with contacts

UL technical data

UL degree of protection Type 1, 2, 3R, 4, 4X, 12, 12K

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+60

Storage temperature

min	°C	-40
max	°C	+70

Certifications and compliance

Compliance

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-5-1
- UL508

Certificates

cULus

ETIM classification

ETIM 8.0

EC002498 -
Accessories/spare
parts for low-
voltage switch
technology