



## Features

Use: Indoor  
 Type of installation: TRACK  
 Emission: ADJUSTABLE  
 Optics: SPOT  
 Beam: 34°  
 Colour: BLACK  
 Dimming: DALI  
 Emergency: NO  
 L: 255mm  
 A: Ø55mm  
 H: 60mm  
 Made in: ITALY  
 Warranty: 5 years  
 Weight: 0.55kg

## Tech data

Luminaire input power: 15W  
 Luminaire luminous flux: 1226lm  
 IP: 20  
 Insulation class: II  
 Supply voltage: 220-240V 50/60Hz  
 SELV: Si

## Source

Light source: LED  
 Source power: 12W  
 Source luminous flux: 1520lm  
 Colour temperature: 4000K  
 CRI: >90  
 Colour tolerance: 2 Step MacAdam  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



# GALA

101885.02

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

---



GALA: HONEYCOMB D.50

**1018A4.02**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.