


Part number

# PEW 12595 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + N + PE, 9 h (blue), 125 A, 120/208 ÷ 144/250 V, inclined

#### Product description

<b>Product type</b>	Socket Flush-mounting
<b>Series</b>	PEW...PI, PLUSO
<b>N. of poles</b>	3 poles + N + 
<b>Clock position</b>	9
<b>Specification</b>	Inclined

#### Technical data

<b>Current</b>	125 A
<b>Voltage</b>	120/208 ÷ 144/250 V
<b>IP degree of protection</b>	IP67

#### Further technical details

<b>Weight</b>	1.677,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 5015 blue
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747071260
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	150,00 mm
<b>Packaging height</b>	140,00 mm
<b>Packaging width</b>	180,00 mm
<b>Packaging weight</b>	1,79 kg
<b>Packaging volume</b>	3,78 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	1 Pcs
<b>Packaging EAN code</b>	8015747071277


Part number

# PEW 12595 PI



Catalogue drawings

( 63 /125A) PEW ... PI



PEW ... PI	A	B	C	D	E	F	G	H	I	X	Y
<b>63A</b> 2P+⊕	100	107	124	84	55	107	82	45	94	77	85
3P+⊕	100	107	124	84	55	107	82	45	94	77	85
3P+N+⊕	100	107	124	84	55	107	82	45	94	77	85
<b>125A</b> 2P+⊕	130	130	143	94	87	119	102	56	112	104	104
3P+⊕	130	130	143	94	87	119	102	56	112	104	104
3P+N+⊕	130	130	143	94	87	119	102	56	112	104	104

## Notes

Dimensions shown in mm are not binding and may be changed without notice.

- Compliant with EN 60309-1 and -2
- Enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
- RAL 7035 grey enclosure, spring lid colour coded according to the operating voltage
- Flange with anti-ageing gasket
- PE...PI types (IP44), spring lid
- PEW...PI types (IP67), spring lid with locking ring and gasket
- Terminals with retained screws
- 63A, 125A: with pilot contact
- Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickel-plated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.
- IP44 and IP67 degrees of protection (EN 60529)